

Wetlands Bureau Decision Report

Decisions Taken
04/10/2006 to 04/16/2006

DISCLAIMER:

This document is published for information purposes only and does not constitute an authorization to conduct work. Work in jurisdiction may not commence until the applicant has received a posting permit.

Decisions are subject to appeal, and are reviewed by the federal agencies for compliance with Section 404 of the Federal Clean Water Act.

APPEAL:

I. Any affected party may ask for reconsideration of a permit decision in accordance with RSA 482-A:10,II within 20 days of the Department's issuance of a decision. Requests for reconsideration should:

- 1) describe in detail each ground for complaint. Only grounds set forth in the request for reconsideration can be considered at subsequent levels of appeal;
- 2) provide new evidence or information to support the requested action;
- 3) Parties other than the applicant, the town, or contiguous abutters must explain why they believe they are affected; and
- 4) Be mailed to the DES Wetlands Bureau, PO Box 95, Concord, NH 03302-0095.

II. An appeal of a decision of the department after reconsideration may be filed with the Wetlands Council in accordance with RSA 482-A:10, IV within 30 days of the department's decision. Filing of the appeal must:

- 1) be made by certified mail to Brian Fowler, Chairperson, Wetlands Council, PO Box 95, Concord, NH 03302-0095 (a copy should also be sent to the DES Wetlands Bureau);
- 2) contain a detailed description of the land involved in the department's decision; and
- 3) set forth every ground upon which it is claimed that the department's decision is unlawful or unreasonable.

MAJOR IMPACT PROJECT

2004-02965 NEWPORT GOLF CLUB
NEWPORT Sugar River

Requested Action:

Restore approximately 56,000 square feet (1,400 linear feet) of the bed and banks of the South Branch of the Sugar River to its historic channel and fill approximately 18,400 square feet (460 linear feet) within the bed and banks of the South Branch of the Sugar River. Dredge approximately 11,442 square feet of palustrine emergent, wet meadow to create additional flood storage. Work to include installation of in-stream structures and the establishment of a 35 foot wide vegetated riparian buffer along the restored stream channel.

Conservation Commission/Staff Comments:

No comments submitted from the conservation commission.

Inspection Date: 04/22/2005 by Jeffrey D Blecharczyk

APPROVE PERMIT:

Restore approximately 56,000 square feet (1,400 linear feet) of the bed and banks of the South Branch of the Sugar River to its historic channel and fill approximately 18,400 square feet (460 linear feet) within the bed and banks of the South Branch of the Sugar River. Dredge approximately 11,442 square feet of palustrine emergent, wet meadow to create additional flood storage. Work to include installation of in-stream structures and the establishment of a 35 foot wide vegetated riparian buffer along the restored stream channel.

With Conditions:

1. All work shall be in accordance with plans by Holden Engineering & Surveying, Inc. (Concord Office), sheets 1, 7, 10 and 11 of 13 dated 01-19-06, sheet 2 of 13 dated 10-14-03, sheets 8, 9, and 12 of 13 dated 03-01-06, as received by the Department on March 9, 2006, and sheets 6 and 13 of 13 dated 04-05-06, as received by the Department on April 6, 2006, and the Construction Sequence and Riparian Buffer details prepared by Holden Engineering & Surveying, Inc. (Bedford Office) dated April 4, 2006, as received by the Department on April 4, 2006.
2. This permit shall not be effective until it has been recorded with the county Registry of Deeds office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to construction.
3. At least 48 hours prior to the start of construction, a pre-construction meeting shall be held with NHDES Land Resources Management Program staff at the project site to review the conditions of this wetlands permit. It shall be the responsibility of the permittee to schedule the pre-construction meeting, and the meeting shall be attended by the permittee, his/her professional engineer(s), wetlands scientist(s), and the contractor(s) responsible for performing the work.
4. The permittee shall notify DES and the local conservation commission in writing of their intention to commence construction no less than 5 business days prior to construction.
5. Construction shall be inspected daily by a qualified wetland scientist, erosion control specialist, or professional engineer to ensure that appropriate protective measures are properly implemented, including those outlined in the plans and documents supporting this permit application and the conditions of this authorization. The findings of these inspections shall be documented and maintained on-site. The inspection reports shall include remedial measures necessary to assure compliance with the plans and permit conditions.
6. The applicant shall receive approval for a turbidity monitoring plan from the Watershed Management Bureau prior to construction. The plan shall include in-stream monitoring which will determine compliance with the state water quality standard (Class B) for turbidity. The monitoring shall include the establishment of background turbidity levels to assess the level of change during reintroduction of flows into the restored stream channel.
7. Work shall be done during low flow.
8. Work shall be conducted in a manner so as to minimize turbidity and sedimentation to surface waters and wetlands.
9. Work shall be conducted in a manner that avoids excessive discharges of sediments to fish spawning areas.
10. Appropriate siltation and erosion controls shall be in place prior to construction, shall be maintained during construction, and

remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.

11. Appropriate turbidity controls shall be installed prior to construction, shall be maintained during construction such that no turbidity escapes the immediate dredge area, and shall remain until suspended particles have settled and the water at the work site has returned to normal clarity.
12. Unconfined work within the river, exclusive of work associated with installation of a cofferdam, shall be done during periods of low flow.
13. Cofferdams shall not be installed during periods of high flow, whether due to seasonal runoff or precipitation. Once a cofferdam is fully effective, confined work can proceed without restriction.
14. Temporary cofferdams shall be removed in a controlled, gradual manner that does not allow a sudden release of impounded water so as to cause erosion or siltation.
15. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
16. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid prior to entering surface waters or wetlands.
17. Faulty equipment shall be repaired prior to entering jurisdictional areas.
18. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
19. All refueling of equipment shall occur outside of surface waters or wetlands during construction.
20. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
21. Restoration of the river banks, bed and riparian buffer shall be properly constructed, landscaped, monitored and remedial actions taken that may be necessary to create a functioning, stable riverine system representative of existing reaches along the South Branch of the Sugar River through the golf course. Remedial measures may include replanting, relocating plantings, removal of invasive species, and changing the location, orientation and configuration of in-stream structures.
22. The permittee shall designate a qualified professional who will be responsible for monitoring and ensuring that the riverine and riparian buffer restoration areas are constructed in accordance with the plans. Monitoring shall be accomplished in a timely fashion and remedial measures taken if necessary. The Wetlands Bureau shall be notified in writing of the designated professional prior to the start of work and if there is a change of status during the project.
23. The designated qualified professional shall conduct a follow-up inspection after the first growing season, to review the success of the riverine and riparian buffer restoration areas and schedule remedial actions if necessary. A report outlining these follow-up measures and a schedule for completing the remedial work shall be submitted by December 1 of that year. Similar inspections, reports and remedial actions shall be undertaken in at least the second and third years following the completion of the riverine restoration.
24. The riparian buffer restoration areas shall have at least 75% successful establishment of vegetation after two (2) growing seasons, or shall be replanted and re-established until a functional riparian buffer is replicated in a manner satisfactory to the DES Wetlands Bureau.
25. The permittee shall attempt to control invasive, weedy species such as purple loosestrife (*Lythrum salicaria*) and common reed (*Phragmites australis*) by measures agreed upon by the Wetlands Bureau if the species is found in the mitigation areas during construction and during the early stages of vegetative establishment.
26. A post-construction report documenting the status of the completed project with photographs shall be submitted to the Wetlands Bureau within 60 days of the completion of construction.
27. Within three days of final grading in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
28. Where construction activities have been temporarily suspended within the growing season, all exposed soil areas shall be stabilized within 14 days by seeding and mulching.
29. Where construction activities have been temporarily suspended outside the growing season, all exposed areas shall be stabilized within 14 days by mulching and tack. Slopes steeper than 3:1 shall be stabilized by matting and pinning.
30. Any future work on this property that is within the jurisdiction of the DES Wetlands Bureau as specified in RSA 482-A will require a new application and approval by the Bureau.
31. Within the re-established driving range on the south end of the golf course, bordering the Sugar River, the riparian buffer shall be permanently maintained, and placement of additional fill, construction of structures, or storage of vehicles or hazardous materials shall be prohibited.
32. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a major impact project per Administrative Rule Wt 303.02(i), alteration of more than 200 linear feet of a perennial nontidal stream and/or its banks.
2. The need for the proposed impacts has been demonstrated by the applicant per Wt 302.01.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Wt 302.04(a), Requirements for Application Evaluation, has been considered in the design of the project.
5. DES Staff conducted a field inspection of the proposed project on April 22, 2005. Field inspection determined initial project designs require additional review and potential alterations.
6. Subsequent design changes to the initial proposal reduced the scope of the project to restoration of the historic channel only.
7. The project will impact approximately 29,400 sq ft of jurisdictional wetlands and riverine habitat and therefore requires mitigation.
8. The project will create approximately 56,000 sq ft of riverine habitat.
9. The applicant is required to create 1.5 times the impacted wetlands for mitigation. The proposed impacts, 29,400 sq ft requires 44,100 sq ft of created wetlands. The project will create approximately 56,000 sq ft of wetlands or 1.9 times the proposed impacts.
10. The project will alter approximately 460 linear ft of stream channel to create approximately 1,400 linear ft of stream channel, for a net gain of approximately 940 linear feet of stream channel and riparian habitat.
11. The NHF&G Department requested a minimum 25 foot native, vegetated riparian buffer be established.
12. The applicant as provided for a 35 foot wide native vegetated riparian buffer.
13. The public hearing is waived with the finding that the project impacts will not significantly impair the resources of this riverine system.

2005-00837 SANDOWN, TOWN OF
SANDOWN Exeter River

Requested Action:

Deny request to dredge and fill 2165 square feet to repair existing bridge.

DENY PERMIT-INSUFFICIENT & UNTIMELY RESP:

Deny request to dredge and fill 2165 square feet to repair existing bridge.

With Findings:

1. A request for additional information dated July 6, 2005, addressed to the applicant and copied to the agent of record, clearly identified changes made to RSA 482-A:3 in 2003, requiring the applicant to submit additional information to DES within 120 days of the request.
2. Pursuant to RSA 482-A, XIV(b), if the requested additional information is not received by DES within 120 days of the request, DES shall deny the application.
3. DES did not receive the requested additional information within the 120 days and therefore the application has been denied.

2005-02502 VAN SICKLE 1994 TRUST, ALDEN
ASHLAND Squam River

Requested Action:

Reconfigure a 101 slip major docking facility, repair and renovate the 4 existing boathouses, repair 145 ft of existing retaining wall and upgrade the site with improved drainage, plantings and erosion controls on the Squam River, Ashland.

Conservation Commission/Staff Comments:

No Com Com comments by January 3, 2006

Inspection Date: 03/31/2006 by Dale R Keirstead

APPROVE PERMIT:

Reconfigure a 101 slip major docking facility, repair and renovate the 4 existing boathouses, repair 145 ft of existing retaining wall and upgrade the site with improved drainage, plantings and erosion controls on the Squam River, Ashland.

With Conditions:

1. All work shall be in accordance with plans by Rist-Frost Shumway dated March 31, 2006, as received by the Department on April 4, 2006, Shed plans by David Driscoll Design dated September 28, 2005, as received by the Department on October 17, 2005, Kesumpe Boathouse plans by David Driscoll Design dated September 28, 2005, revision date March 8, 2006, as received by the Department on March 8, 2006, Asquam Boathouse plans by David Driscoll Design dated September 28, 2005, revision date March 8, 2006, as received by the Department on March 8, 2006, Halcyon Boathouse plans by David Driscoll Design dated September 28, 2005, revision date February 1, 2006, as received by the Department on February 10, 2006, and Livermore Boathouse plans by David Driscoll Design dated September 28, 2005, revision date February 1, 2006, as received by the Department on February 10, 2006.
2. This permit shall not be effective until it has been recorded with the Registry of Deeds Office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to construction.
3. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
4. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
5. Within three days of final grading in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
6. Where construction activities have been temporarily suspended within the growing season, all exposed soil areas shall be stabilized within 14 days by seeding and mulching.
7. Where construction activities have been temporarily suspended outside the growing season, all exposed areas shall be stabilized within 14 days by mulching and tack. Slopes steeper than 3:1 shall be stabilized by matting and pinning.
8. Silt fencing must be removed once the area is stabilized.
9. Construction debris and material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
10. The owner shall file a restrictive covenant in the appropriate registry of deeds, with each appropriate deed, limiting the use of the boathouse to the storage of boats and boating-related accessories. A copy of the recorded covenant permit shall be submitted to the DES Wetlands Bureau prior to construction.
11. Boathouse repairs shall maintain existing size, location and configuration.
12. This permit does not allow for maintenance dredging.
13. Repairs to these structures may be conducted, as necessary, throughout the duration of this permit provided that the permittee notifies the Wetlands Bureau and Conservation Commission, in writing, of the proposed start and completion date prior to performing any repair.
14. Work authorized shall be carried out such that discharges in spawning or nursery areas during spawning seasons shall be avoided, and impacts to such areas shall be avoided or minimized to the maximum extent practicable during all times of the year.
15. Work shall be carried out in a time and manner such that there will be no disturbance to migratory waterfowl breeding areas or fish spawning areas.
16. Work shall be done during low flow.
17. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This project is classified as a major project per Rule Wt 303.02(d), modification of a major docking facility.
2. The re-configuration of the docking facility will not increase the number of slips or the location of the docks in this grandfathered docking facility along Squam River.
3. The proposed work will improve the shoreline stability and help prevent further erosion along a highly impacted area on the Squam River.
4. Public hearing is waived based on field inspection, by NH DES staff, on March 31, 2006, with the finding that the project

impacts will not significantly impair the resources of the Squam River.

-Send to Governor and Executive Council-

2005-02516 OSSIPEE LAKE MARINA INC
FREEDOM Ossipee Lake

Requested Action:

Repair and upgrade an existing boatramp by adding a 12 ft by 10 ft extension of the ramp surface using concrete logs with 1 1/2 stone to reduce erosion of the lakebed on Ossipee Lake, Ossipee.

Conservation Commission/Staff Comments:

Con Com has concerns about Milfoil and request assistance by a limnologist.

NH Fish and Game will not be submitting comments, NH NHI has not submitted comments by January 12, 2006

Inspection Date: 03/31/2006 by Dale R Keirstead

APPROVE PERMIT:

Repair and upgrade an existing boatramp by adding a 12 ft by 10 ft extension of the ramp surface using concrete logs with 1 1/2 stone to reduce erosion of the lakebed on Ossipee Lake, Ossipee.

With Conditions:

1. All work shall be in accordance with plan as received by the Department on April 7, 2006.
2. This permit shall not be effective until it has been recorded with the Registry of Deeds Office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to construction.
3. Any further alteration of areas on this property that are within the jurisdiction of the DES Wetlands Bureau will require a new application and further permitting by the Bureau.
4. This permit to replace or repair existing structures shall not preclude the Department of Environmental Services from taking any enforcement action or revocation action if the Department of Environmental Services later determines that these "existing structures" were not previously permitted or grandfathered.
5. Appropriate turbidity controls shall be installed prior to construction, shall be maintained during construction such that no turbidity escapes the immediate dredge area, and shall remain until suspended particles have settled and the water at the work site has returned to normal clarity.
6. Appropriate siltation and erosion controls shall be in place prior to construction, shall be maintained during construction, and shall remain until the area is stabilized.
7. This permit does not allow for any dredging of material from the lakebed.
8. The extension of the boatramp shall not extend more than 10 ft lakeward from the existing ramp.
9. The stone placed for the base of the ramp extension shall not extend beyond the limits on the approved plan.
10. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minimum impact project per Administrative Rule Wt 303.04(o), projects deemed minimum impact by the department based on the degree of environmental impact.
2. The need for the proposed impacts has been demonstrated by the applicant per Wt 302.01.
3. Field inspection by the Department found the proposed plan to be the least impacting to the lakebed. The proposed plan will help limit the damage caused by power loading in this sensitive, narrow channel.
4. The applicant has removed the request to dredge the area and thus the local Conservation Commission and the Ossipee Lake Alliance concerns have been addressed.

MINOR IMPACT PROJECT

**2005-00478 HOYT REAL ESTATE TRUST
DANVILLE Unnamed Wetland**

Requested Action:

Deny request to dredge and fill 11400 square feet of wetland for access in the subdivision of 76.03 acres into 24 single family lots.

DENY PERMIT-INSUFFICIENT & UNTIMELY RESP:

Deny request to dredge and fill 11400 square feet of wetland for access in the subdivision of 76.03 acres into 24 single family lots.

With Findings:

1. A request for additional information dated May 27, 2005, addressed to the applicant and copied to the agent of record, clearly identified changes made to RSA 482-A:3 in 2003, requiring the applicant to submit additional information to DES within 120 days of the request.
2. Pursuant to RSA 482-A, XIV(b), if the requested additional information is not received by DES within 120 days of the request, DES shall deny the application.
3. DES did not receive the requested additional information within the 120 days and therefore the application has been denied.

**2005-02601 LEATHERS, FREDRICK
LACONIA Lake Winnepesaukee**

Requested Action:

Remove an 6 ft by 70 ft permanent dock and non-conforming deck and construct a 6 f by 75 ft 6 in permanent piling supported dock accessed by a 6 ft by 7 ft permanent walkway along the shore, install one three pile ice cluster, install permanent boatlift in the western slip with a 14 ft by 30 ft seasonal canopy, install two seasonal PWC lifts on the western side of the dock providing two boatslips on an average of 100 ft of frontage on Lake Winnepesaukee, Laconia.

Conservation Commission/Staff Comments:

No Con Com comments by January 4, 2006.

Inspection Date: 04/04/2006 by Dale R Keirstead

APPROVE PERMIT:

Remove an 6 ft by 70 ft permanent dock and non-conforming deck and construct a 6 f by 75 ft 6 in permanent piling supported dock accessed by a 6 ft by 7 ft permanent walkway along the shore, install one three pile ice cluster, install permanent boatlift in the western slip with a 14 ft by 30 ft seasonal canopy, install two seasonal PWC lifts on the western side of the dock providing two boatslips on an average of 100 ft of frontage on Lake Winnepesaukee, Laconia.

With Conditions:

1. All work shall be in accordance with plans by Watermark Marine Construction dated October 7, 2005, revision date April 7, 2006, as received by the Department on April 7, 2006.
2. This permit shall not be effective until it has been recorded with the Registry of Deeds Office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to construction.
3. This permit to replace or repair existing structures shall not preclude the Department of Environmental Services from taking any enforcement action or revocation action if the Department of Environmental Services later determines that these "existing structures" were not previously permitted or grandfathered.

4. The existing deck shall be reduced to the permitted 6 ft x 7ft walkway dimensions prior to the lengthening of the pier.
5. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, maintained during construction, and shall remain until the area is stabilized.
6. Work authorized shall be carried out such that discharges in spawning or nursery areas during spawning seasons shall be avoided, and impacts to such areas shall be avoided or minimized to the maximum extent practicable during all times of the year.
7. Work shall be carried out in a time and manner such that disturbance to migratory waterfowl breeding areas and spawning areas shall be avoided.
8. Additional expedited minimum impact applications shall be accepted for the subject property for a period of 12 months only if the applicant demonstrates by plan that the additional project(s) are wholly unrelated or separate from the original application and when considered with the original application are not classified as minor or major.
9. Canopies shall be of seasonal construction type with a flexible fabric cover which shall be removed for the non-boating season.
10. Seasonal PWC lifts shall be of seasonal construction type which shall be removed for the non-boating season.
11. This permit does not allow for maintenance dredging.
12. Repairs to these structures may be conducted, as necessary, throughout the duration of this permit provided that the permittee notifies the Wetlands Bureau and Conservation Commission, in writing, of the proposed start and completion date prior to performing any repair.
13. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minor impact project per Administrative Rule Wt 303.03(d), construction or modification of a docking facility that exceeds the design and construction criteria discussed at Wt 402.01.
2. The need for the proposed impacts has been demonstrated by the applicant per Wt 302.01.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Wt 302.03.
4. DES Staff conducted a field inspection of the proposed project on April 4, 2006. Field inspection determined the proposed project will not adversely affect Lake Winnepesaukee.
5. The proposed project brings a non-conforming docking structure into compliance.
6. The Applicant has reduced the deck to a 6 ft wide walkway in order to meet the requirements on Rule Wt 402.20.

2006-00013 HALL, SCOTT
JEFFERSON Unnamed Wetland

Requested Action:

Dredge and fill 8,125 square feet of forested wetlands along the thread of 25 linear feet of perennial stream to install a 30-inch x 20-foot culvert for driveway access to a single family residence.

APPROVE PERMIT:

Dredge and fill 8,125 square feet of forested wetlands for driveway access to a single family residence, further described as follows:

1. Install a 48-inch x 20-foot embedded culvert along the thread of 25 linear feet of perennial stream; and
2. Install three 15-inch x 30-foot HDPE culverts to maintain wetland hydrologic connectivity.

With Conditions:

1. All work shall be in accordance with plans by Watershed to Wildlife, Inc. dated March 2006, as received by the Department on April 03, 2006.
2. This permit is contingent on approval by the DES Subsurface Systems Bureau.
3. This permit is contingent on review and approval, by the DES Wetlands Bureau, of final stream diversion/erosion control plans. Those plans shall detail the timing and method of stream flow diversion during construction, and show temporary siltation/erosion/turbidity control measures to be implemented.
4. Work shall be done during annual low flow conditions and during the months of May through September. No in-stream work shall occur after October 1 unless a waiver of this condition is issued by the DES Wetlands Bureau in consultation with the NH Department of Fish and Game.
5. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction,

and remain until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.

6. Work shall be conducted in a manner so as to minimize turbidity and sedimentation.
7. Orange construction fencing shall be placed at the limits of construction to prevent accidental encroachment on wetlands.
8. Prior to commencing work within the channel, a cofferdam shall be constructed to isolate the work area from the surface waters.
9. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
10. No work within the confined area shall proceed until the cofferdam is fully effective, and water flow is controlled.
11. Temporary cofferdams shall be entirely removed immediately following construction.
12. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
13. Connectivity culverts shall be laid at original grade.
14. Proper headwalls shall be constructed within seven days of culvert installation.
15. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).
16. Native material removed from the streambed during culvert installation, shall be stockpiled separately and reused to emulate a natural channel bottom within the culvert. Any new materials used must be similar to the natural stream substrate and shall not include angular rip-rap.
17. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid prior to entering surface waters or wetlands. Faulty equipment shall be repaired prior to entering jurisdictional areas.
18. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
19. All refueling of equipment shall occur outside of surface waters or wetlands during construction.
20. Banks shall be restored to their original grades and to a stable condition within three days of completion of construction.
21. Extreme precautions shall be taken within riparian areas to limit unnecessary removal of vegetation during access road construction and areas cleared of vegetation to be revegetated with native like species within three days of the completion of this project.
22. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting on slopes steeper than 3:1.

With Findings:

1. This is a minor impact project per Administrative Rule Wt 303.03(1), alteration of less than 200 linear feet of a perennial stream channel or its banks.
2. The applicant provided an embedded culvert at the perennial stream crossing to maintain a natural stream bottom.
3. The applicant provided three hydrologic connectivity culverts along the approximate 350 linear foot proposed driveway.
4. No comments were submitted from the Jefferson Conservation Commission, NH Fish and Game Department, or the NH Natural Heritage Bureau.
5. The need for the proposed impacts has been demonstrated by the applicant per Wt 302.01.
6. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Wt 302.03.
7. The applicant has demonstrated by plan and example that each factor listed in Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.

2006-00033 PETERBOROUGH, TOWN OF
PETERBOROUGH Otter Brook

Requested Action:

Dredge and fill 1,424 square feet of riverine, palustrine emergent, and palustrine scrub-shrub wetlands to reconstruct an existing

bridge with associated wingwalls, abutments, and rip-rap protection impacting 8 additional feet in the banks of the channel (the existing abutments will remain in place and be tied into the new structure); construction of an 8-foot long retaining wall to connect an existing retaining wall with the concrete platform of the bridge; and conduct associated road improvements including regrading of road side-slopes, installation of guard rails, and replacement of a 15-inch x 36-foot culvert and associated inlet and outlet protection.

Inspection Date: 11/29/2005 by Christine Bowman

APPROVE PERMIT:

Dredge and fill 1,424 square feet of riverine, palustrine emergent, and palustrine scrub-shrub wetlands to reconstruct an existing bridge with associated wingwalls, abutments, and rip-rap protection impacting 8 additional feet in the banks of the channel (the existing abutments will remain in place and be tied into the new structure); construction of an 8-foot long retaining wall to connect an existing retaining wall with the concrete platform of the bridge; and conduct associated road improvements including regrading of road side-slopes, installation of guard rails, and replacement of a 15-inch x 36-foot culvert and associated inlet and outlet protection.

With Conditions:

1. All work shall be in accordance with plans by Edwards and Kelcey dated November 2005, as received by the DES Wetlands Bureau on January 5, 2006.
2. Any future work on this property that is within the jurisdiction of the DES Wetlands Bureau as specified in RSA 482-A will require a new application and approval by the Bureau.
3. All work shall be done during low flow.
4. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized.
5. Appropriate turbidity controls shall be installed prior to construction, shall be maintained during construction such that no turbidity escapes the immediate dredge area, and shall remain until suspended particles have settled and the water at the work site has returned to normal clarity.
6. Silt fence(s) must be removed once the area is stabilized.
7. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).
8. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
9. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
10. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
11. Construction shall be inspected by a certified wetland scientist, erosion control specialist, or professional engineer to ensure that appropriate protective measures are properly implemented, including those outlined in the plans and documents supporting this permit application and the conditions of this authorization.
12. Proper headwalls shall be constructed within seven days of culvert installation.
13. Orange construction fencing shall be placed at the limits of construction to prevent accidental encroachment on wetlands.
14. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid prior to entering surface waters or wetlands.
15. Faulty equipment shall be repaired prior to entering jurisdictional areas.
16. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
17. All refueling of equipment shall occur outside of surface waters or wetlands during construction.

With Findings:

1. This is a minor impact project per Administrative Rule Wt 303.03(h), Projects involving less than 20,000 square feet of alteration in the aggregate in nontidal wetlands, nontidal surface waters, or banks adjacent to nontidal surface waters which exceed

the criteria of Wt 303.04(f).

2. The need for the proposed impacts has been demonstrated by the applicant per Wt 302.01. The existing bridge, constructed in 1940, is a single-span structure approximately 23.5 feet in length and 18 feet wide curb-to-curb with inadequate guard rails and a sharp vertical curve in the approach. The 18-foot width of the bridge creates a "neck-down" effect as vehicles approach the bridge. Reconstruction of the bridge and the associated road improvements will provide safe access by improving the sharp vertical curve in the approach, improving sight distance, and providing a wider travel surface with adequate guard rails.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the DES Wetlands Bureau's jurisdiction per Wt 302.03. Reconstruction of the bridge in the existing location is the least-impacting alternative because it maintains the existing road alignment and minimizes impacts to Otter Brook and the adjacent pond and wetlands. The new bridge abutments will be constructed on the outside of the existing abutments and the existing abutments will be tied into the new structure. The stream bed will not be disturbed to remove the existing abutments. The existing flow path of the stream will be maintained and flows will not be altered.
4. The applicant has demonstrated by plan and example that each factor listed in Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.
5. The bridge is being replaced under the NHDOT Municipally Managed Bridge Program.
6. The bridge crosses Otter Brook approximately 1.7 miles upstream from the confluence with the Contoocook River. Immediately upstream of the bridge is a concrete dam with retaining walls that impounds Otter Brook into a pond.
7. The project will not disturb the dam immediately upstream of the bridge.
8. Along the bank of the pond is a two foot high stone masonry retaining wall that extends from the dam for approximately 45 feet. The proposed retaining wall will connect the existing retaining wall to the concrete platform of the bridge.
9. All proposed work is being conducted within the road right-of-way.
10. During reconstruction of the bridge, the road will be closed and a detour route indicated.
11. The Nongame and Endangered Wildlife Program of the NH Fish and Game Department did not have record of any rare or endangered species near the project area.

2006-00070 ROSBOROUGH, JAMES
NOTTINGHAM Patuckaway Lake

Requested Action:

Construct a 6 ft by 30 ft seasonal dock providing two boatslips adjacent to and existing 10 ft by 20 ft boathouse on an average of 205 ft of frontage on Pawtuckaway Lake, Nottingham.

Conservation Commission/Staff Comments:

No comments from Con Com by April 11, 2006.

NH

APPROVE PERMIT:

Construct a 6 ft by 30 ft seasonal dock providing two boatslips adjacent to and existing 10 ft by 20 ft boathouse on an average of 205 ft of frontage on Pawtuckaway Lake, Nottingham.

With Conditions:

1. All work shall be in accordance with plans as received by the Department on January 11, 2006.
2. This permit shall not be effective until it has been recorded with the Registry of Deeds Office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to installation.
3. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
4. This shall be the only structure on this water frontage and all portions of the dock shall be at least 20 ft. from abutting property lines or the imaginary extension of those lines into the water.
5. Seasonal pier shall be removed from the lake for the non-boating season.
6. No portion of the pier shall extend more than 30 feet from the shoreline at full lake elevation.
7. These shall be the only structures on this water frontage and all portions of the dock shall be at least 20 ft. from the abutting property lines or the imaginary extension of those lines into the water.

8. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minor impact project per Administrative Rule Wt 303.03(d), construction of a docking structure which exceeds the design and construction criteria discussed at Wt 402.01 for minimum projects.
2. The applicant is not modifying the existing boathouse.

**2006-00518 DONARUMO REALTY TRUST
MADISON Unnamed Wetland**

Requested Action:

Fill 7,024 square feet of wetlands to construct an access road on a 52-acre lot for a residential subdivision.

APPROVE PERMIT:

Fill 7,024 square feet of wetlands to construct an access road on a 52-acre lot for a residential subdivision.

With Conditions:

1. All work shall be in accordance with revised plans by Holden Engineering & Surveying dated February 27, 2006, as received by the Department on March 10, 2006.
2. There shall be no further alteration of wetlands for lot development, driveways, culverts, or for septic setback.
3. The deed which accompanies the sales transaction for each of the lots in this subdivision shall contain condition #2 of this approval.
4. This permit shall not be effective until it has been recorded with the Registry of Deeds Office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau.
5. This permit is contingent on approval by the DES Site Specific Program.
6. This permit is contingent on approval by the DES Subsurface Systems Bureau.
7. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and shall remain until the area is stabilized.
8. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
9. Work shall be done during low flow.
10. Culvert outlets shall be protected in accordance with the DES Best Management Practices for Urban Stormwater Runoff Manual (January 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August 1992).
11. Within three days of final grading in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
12. Where construction activities have been temporarily suspended within the growing season, all exposed soil areas shall be stabilized within 14 days by seeding and mulching.
13. Where construction activities have been temporarily suspended outside the growing season, all exposed areas shall be stabilized within 14 days by mulching and tack. Slopes steeper than 3:1 shall be stabilized by matting and pinning.
14. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).

With Findings:

1. This is a Minor Project per NH Administrative Rule Wt 303.03(h), as wetland impacts are less than 20,000 square feet.
2. The need for the proposed impacts has been demonstrated by the applicant per Rule Wt 302.01.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Rule Wt 302.03.

4. The applicant has demonstrated by plan and example that each factor listed in Rule Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.

MINIMUM IMPACT PROJECT

2005-00779 NH DEPT OF TRANSPORTATION
CHESTERFIELD Spofford Lake

Requested Action:

NHDOT requests amendment to replace a 36 in. x 40 ft. culvert with twin 36 in. x 50 ft. culverts instead of twin 30 in. x 40 ft. culverts and construct new headwalls temporarily impacting 130 sq. ft. of stream and banks.

APPROVE AMENDMENT:

Amend permit to read:

Replace a 36 in. x 40 ft. culvert with twin 36 in. x 50 ft. culverts and construct new headwalls temporarily impacting 130 sq. ft. of stream and banks.

With Conditions:

With amended conditions:

1. All work shall be in accordance with plans by NHDOT Maintenance District 4 dated 04/06 as received by the Department on April 11, 2006.
2. Dredged material shall be placed out of the DES Wetlands Bureau jurisdiction.
3. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and shall remain until the area is stabilized.
4. Construction equipment shall not be located within surface waters.
5. Within three days of final grading in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
6. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).
7. Extreme precautions to be taken within riparian areas to limit unnecessary removal of vegetation during road construction and areas cleared of vegetation to be revegetated as quickly as possible.
8. There shall be no further alteration to wetlands or surface waters without amendment of this permit.
9. Proper headwalls shall be constructed within seven days of culvert installation.
10. Work shall be done during low flow.

2005-02219 NH DEPT OF TRANSPORTATION
WAKEFIELD Jenness Brook

Requested Action:

Dredge 1,200 sq. ft. and conduct temporary impacts within 400 sq. ft. to remove material at the outlet end of existing 15" and 24" culverts and construct a 3' x 4' stone header with Class C stone 50 feet on either side of the header to stabilize the banks at the outlet of an existing 15" culvert. NHDOT project #M312-5.

APPROVE PERMIT:

Dredge 1,200 sq. ft. and conduct temporary impacts within 400 sq. ft. to remove material at the outlet end of existing 15" and 24" culverts and construct a 3' x 4' stone header with Class C stone 50 feet on either side of the header to stabilize the banks at the outlet of an existing 15" culvert. NHDOT project #M312-5.

With Conditions:

1. All work shall be in accordance with plans by NHDOT dated 7/15/05, as received by the Department on 9/20/05.
2. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
3. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
4. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
5. Silt fencing must be removed once the area is stabilized.
6. Work shall be done during low flow or dry conditions.
7. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August 1992).

**2005-02852 NH DEPT OF TRANSPORTATION
AUBURN Lake Massabesic**

Requested Action:

NHDOT requests amendment to replace 12 in. culvert under road instead of retaining it in-kind.

Conservation Commission/Staff Comments:

Cons. Comm. no comment

APPROVE AMENDMENT:

Amend permit to read:

Replace 12 in. culvert under road, replace 12 in. culvert along road shoulder, construct a catch basin at a sinkhole site and install a short 12 in. culvert at inlet.

With Conditions:

With amended conditions:

1. All work shall be in accordance with plans by NHDOT revised 1/13/06 as received by the Department on Jan. 19, 2006 to include replacement of the roadway culvert with a 12" plastic culvert.
2. Dredged material shall be placed out of the DES Wetlands Bureau jurisdiction.
3. NO siltation/erosion/turbidity controls shall be placed westerly of the road to protect any sensitive species.
4. The 12" roadway culvert shall be replaced in the exact location with no equipment to disturb existing vegetation along the shore.
5. For any areas on the lake side that will be disturbed, the area shall be raked and any dry/dead vegetation and material piled on one side. This material shall be spread back over the area after the work is completed to help ensure the seed source is returned to the area.
6. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and shall remain until the area is stabilized.
7. The existing grass swale shall remain to provide treatment prior to flow entering the 12 in. culvert.
8. Within three days of final grading in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
9. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).
10. Extreme precautions to be taken within riparian areas to prevent ANY removal of vegetation westerly of the road.

11. There shall be no further alteration to wetlands or surface waters without amendment of this permit.
12. Proper headwalls shall be constructed at the inlet within seven days of culvert installation.
13. Work shall be done during NO flow.

**2006-00076 MORRELL CORPORATION
BARTLETT Unnamed Pond**

Requested Action:

Dredge and fill approximately 1,872 square feet of man-made pond bed and bank, further described as follows:

1. Dredge and fill approximately 72 square feet to replace existing retaining wall and construct new docking structure; and
2. Dredge and fill approximately 1,800 square feet to replace existing riprap with a precast Redi-Rock retaining wall; and
3. Install twin 24-inch x 44-foot culverts.

Conservation Commission/Staff Comments:

1. Con Com is in support of the proposed projects.
2. Three applications (2006-00076, 2006-00077, and 2006-00442) submitted for same applicant, same parcel. File #'s 2006-00077 and 2006-00442 closed and permitted under file #2006-00076.

APPROVE PERMIT:

Dredge and fill approximately 1,872 square feet of man-made pond bed and bank, further described as follows:

1. Dredge and fill approximately 72 square feet to replace existing retaining wall and construct new docking structure; and
2. Dredge and fill approximately 1,800 square feet to replace existing riprap with a precast Redi-Rock retaining wall; and
3. Install twin 24-inch x 44-foot culverts.

With Conditions:

1. All work shall be in accordance with plans by Fernstone Associates dated January 11, 2006; February 03, 2006; and April 04, 2006, as received by the Department on January 17, 2006; March 02, 2006; and April 05, 2006 respectively.
2. All work shall be done in the dry or under draw down conditions.
3. Work shall be conducted in a manner so as to minimize turbidity and sedimentation to surface waters and wetlands.
4. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
5. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
6. Proper headwalls shall be constructed within seven days of culvert installation.
7. Culverts shall be laid at original grade.
8. Machinery shall not be located within surface waters.
9. Machinery shall be staged and refueled in upland areas.
10. There shall be no excavation or operation of construction equipment in flowing water.
11. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
12. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).
13. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
14. Any further alteration of areas on this property that are within the jurisdiction of the DES Wetlands Bureau will require a new application and further permitting by the Bureau.

With Findings:

1. This is a minimum impact project per Administrative Rule Wt 303.04(f), alteration of less than 3,000 square feet of wetlands.
2. Safety concerns have guided the replacement of the existing retaining wall at the swan boat pond and construction of upgraded docking structure.
3. Safety concerns have also guided the construction of the dome pond retaining wall, which is needed to expand the adjacent walkway width from 14 feet to 20 feet.
4. No comments/concerns were submitted from the NH Fish and Game Department or the NH Natural Heritage Bureau.
5. The Bartlett Conservation Commission is in support of the proposed project.
6. The need for the proposed impacts has been demonstrated by the applicant per Wt 302.01.
7. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Wt 302.03.
8. The applicant has demonstrated by plan and example that each factor listed in Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.

2006-00252 VOISINE, DOUGLAS
BARNSTEAD Unnamed Stream

Requested Action:

Dredge and fill 55 square feet of seasonal run-off ditch to install a 12" x 20' driveway culvert feet for access to single family lot.

Conservation Commission/Staff Comments:

Conservation Commission signed expedited.

APPROVE PERMIT:

Dredge and fill 55 square feet of seasonal run-off ditch to install a 12" x 20' driveway culvert feet for access to single family lot.

With Conditions:

1. All work shall be in accordance with plans by Richard Parris dated January 2006, as received by the Department on February 6, 2006.
2. This permit is contingent on approval by the DES Subsurface Systems Bureau.
3. There shall be no further alteration of wetlands for lot development, driveways, culverts, or for septic setback.
4. Appropriate siltation and erosion controls shall be in place prior to construction, maintained during construction, and shall remain until the area is stabilized.
5. Appropriate turbidity controls shall be installed prior to construction, shall be maintained during construction such that no turbidity escapes the immediate dredge area, and shall remain until suspended particles have settled and the water at the work site has returned to normal clarity.
6. Culvert outlets shall be properly rip rapped.
7. Work authorized shall be carried out such that discharges in spawning or nursery areas during spawning seasons shall be avoided, and impacts to such areas shall be avoided or minimized to the maximum extent practicable during all times of the year.
8. Work shall be carried out in a time and manner such that disturbance to migratory waterfowl breeding areas and spawning areas shall be avoided.
9. Additional expedited minimum impact applications shall be accepted for the subject property for a period of 12 months only if the applicant demonstrates by plan that the additional project(s) are wholly unrelated or separate from the original application and when considered with the original application are not classified as minor or major.
10. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.

With Findings:

1. This is a minimum impact project per Administrative Rule Wt 303.04 (z), installation of a culvert and associated fill to permit vehicular access to a piece of property for a single family building.
2. The need for the proposed impacts has been demonstrated by the applicant per Wt 302.01.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project. Locke Lake Colony Association stated in letter received by DES on 3/22/2006, that they are aware of the project, which will occur in the Locke Lake Colony Association roadway right-of-way.

2006-00546 ECKLES, STEVEN
MOULTONBOROUGH Lake Winnepesaukee

Requested Action:

Repair an existing beach retaining wall and construct a wall at the lakeward edge of the beach to perch the beach on Lake Winnepesaukee, Moultonboro.

Conservation Commission/Staff Comments:

No comments from Con Com by April 12, 2006

NH NHI and NH Fish and Game will not be submitting comments

APPROVE PERMIT:

Repair an existing beach retaining wall and construct a wall at the lakeward edge of the beach to perch the beach on Lake Winnepesaukee, Moultonboro.

With Conditions:

1. All work shall be in accordance with plans as received by the Department on March 14, 2006.
2. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
3. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
4. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
5. Repair shall maintain existing size, location and configuration.
6. Retaining wall shall be constructed landward of the shoreline defined by the elevation of normal high water so as not to create land in public water.
7. No more than 10 cubic yards of sand shall be used for replenishment and all sand shall be placed landward of full lake elevation.
8. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minimum impact project per Administrative Rule Wt 303.04(d), construction of a beach.

2006-00557 ERICKSON, DAVID
DEERFIELD Northwood Lake

Requested Action:

Replace an existing 117 linear ft of retain wall consisting of 102 linear ft along the shoreline in the same location on Northwood Lake, Deerfield.

Conservation Commission/Staff Comments:
No comments by Con Com by April 13, 2006

NH NHI has no concerns and NH Fish and Game has not submitted comments by April 13, 2006

APPROVE PERMIT:

Replace an existing 117 linear ft of retain wall consisting of 102 linear ft along the shoreline in the same location on Northwood Lake, Deerfield.

With Conditions:

1. All work shall be in accordance with plans by RSL Layout and Design dated November 28, 2005, as received by the Department on March 16, 2006.
2. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
3. Work shall be done during drawdown.
4. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
5. No equipment shall be operated on or within the lakebed.
6. This permit does not allow for any dredging of the lakebed for access.
7. Area shall be regraded to original contours following completion of work.
8. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
9. Repair shall maintain existing size, location and configuration.
10. Retaining wall shall be constructed landward of the shoreline defined by the elevation of normal high water so as not to create land in public water.
11. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minimum impact project per Administrative Rule Wt 303.04(c), repair or replacement of existing retaining walls performed during drawdown.

**2006-00558 PLOWDEN-WARDLAW REVOC TRUST 2003, ALICE
MOULTONBOROUGH Squam Lake**

Requested Action:

Construct a 6 ft by 20 ft seasonal dock connected to a 6 ft by 20 ft seasonal dock in a "L" shaped configuration attached to a 4 ft by 6 ft concrete pad located behind the natural shoreline accessed by a stair over the bank, install a seasonal boatlift in the lakeward slip provided and install two PWC lifts adjacent to the dock near the shore, with the docking structure providing three boatslips on an average of 190 ft of frontage on Squam Lake, Moultonborough.

Conservation Commission/Staff Comments:
No Con Com comments by April 13, 2006

APPROVE PERMIT:

Construct a 6 ft by 20 ft seasonal dock connected to a 6 ft by 20 ft seasonal dock in a "L" shaped configuration attached to a 4 ft by 6 ft concrete pad located behind the natural shoreline accessed by a stair over the bank, install a seasonal boatlift in the lakeward slip provided and install two PWC lifts adjacent to the dock near the shore, with the docking structure providing three boatslips on an average of 190 ft of frontage on Squam Lake, Moultonborough.

With Conditions:

1. All work shall be in accordance with plans by Watermark Marine Construction dated March 01, 2006, as received by the

Department on March 16, 2006.

2. This permit shall not be effective until it has been recorded with the Registry of Deeds Office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to installation.
3. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
4. This shall be the only structure on this water frontage and all portions of the dock shall be at least 20 ft. from abutting property lines or the imaginary extension of those lines into the water.
5. Seasonal pier shall be removed from the lake for the non-boating season.
6. No portion of the pier shall extend more than 26 feet from the shoreline at full lake elevation.
7. Seasonal boatlift shall be removed from the lake for the non-boating season.
8. Seasonal PWC lift shall be removed from the lake for the non-boating season.
9. The concrete pad shall be located landward of those rocks currently located along the normal high water line. Those rocks existing at the normal high water line shall remain otherwise undisturbed such that the natural shoreline remains identifiable.
10. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minor impact project per Administrative Rule Wt 303.03(d), construction of a docking structure that exceeds the criteria discussed at Wt 402.01 for minimum impact docks classified under Wt 303.04.

FORESTRY NOTIFICATION

2006-00654 LECESSE, PAMELA
PIERMONT Unnamed Stream

COMPLETE NOTIFICATION:
Piermont Tax Map U1, Lot# P56

2006-00722 THERRIEN, EDWARD
CANTERBURY Unnamed Stream

COMPLETE NOTIFICATION:
Canterbury Tax Map 17, Lot# 5

2006-00726 MURRAY SR, JACK
WINCHESTER Unnamed Stream

COMPLETE NOTIFICATION:
Winchester Tax Map 2, Lot# 43

2006-00728 BROWN, ROBERT
NEW LONDON Unnamed Stream

COMPLETE NOTIFICATION:
New London Tax Map 119, Lot# 3

2006-00729 MARTIN, VERNA
WEARE Unnamed Stream

COMPLETE NOTIFICATION:
Weare Tax map 408, Lot# 44

2006-00731 YANKEE CLIPPER COUNAL / BOY SCOUTS OF AMERICA
RAYMOND Unnamed Stream

COMPLETE NOTIFICATION:
Raymond Tax Map 26, Lot# 7

2006-00734 HATHAWAY, SHAUN
MARLOW Unnamed Stream

COMPLETE NOTIFICATION:
Marlow Taxmap 205, Lot# 74

2006-00735 NORTHRUP JR, WILLIAM
HOOKSETT Unnamed Stream

COMPLETE NOTIFICATION:
Hooksett Tax Map 26, Lot# 1

2006-00758 SOUTHWOOD CORP, MICHAEL FALLON
MERRIMACK Unnamed Stream

COMPLETE NOTIFICATION:
Merrimack Tax Map 2B & 2C, Lot# 324, 324-1 & 12, 13

EXPEDITED MINIMUM

2005-00708 WOLF, NANCY
ASHLAND Unnamed Pond

Requested Action:
Deny request to impact 5000 square feet of jurisdiction to repair existing unregistered dam and maintenance dredge pond.

Inspection Date: 01/13/2006 by Jocelyn S Degler

DENY PERMIT-INSUFFICIENT & UNTIMELY RESP:
Deny request to impact 5000 square feet of jurisdiction to repair existing unregistered dam and maintenance dredge pond.

With Findings:

1. A request for additional information dated April 18, 2005, addressed to the applicant and copied to the agent of record, clearly identified changes made to RSA 482-A:3 in 2003, requiring the applicant to submit additional information to DES within 120 days of the request.
2. Pursuant to RSA 482-A, XIV(b), if the requested additional information is not received by DES within 120 days of the request, DES shall deny the application.
3. DES did not receive the requested additional information within the 120 days and therefore the application has been denied.

**2005-02711 HILL, DONALD
BARTLETT Unnamed Stream**

Requested Action:

Repair existing damaged granite box culvert for farming access and clear debris/obstructions from intermittent channel.

APPROVE PERMIT:

Repair existing damaged granite box culvert for farming access and clear debris/obstructions from intermittent channel.

With Conditions:

1. All work shall be in accordance with plans by Donald Hill as received by the Department on November 09, 2005 and March 15, 2006.
2. Work shall be done during low flow conditions.
3. The existing stream bed shall be left intact.
4. Work shall be conducted in a manner so as to minimize turbidity and sedimentation to surface waters and wetlands.
5. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
6. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
7. Any future work on this property that is within the jurisdiction of the DES Wetlands Bureau as specified in RSA 482-A or change of access use to non-farming will require a new application or approval by the Bureau.

With Findings:

1. This is a minimum impact project per Administrative Rule Wt 303.04(x), maintenance, repair, or replacement of a culvert.
2. Access is for farming purposes.
3. The need for the proposed impacts has been demonstrated by the applicant per Wt 302.01.
4. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Wt 302.03.
5. The applicant has demonstrated by plan and example that each factor listed in Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.

**2005-02977 153 CONCORD STAGE DEVELOPMENT LLC
WEARE Unnamed Stream**

Requested Action:

Temporary impact of 318 square feet of an intermittent stream (20 linear feet along the channel centerline) and associated forested wetlands to install two sewer lines to a condominium complex.

Conservation Commission/Staff Comments:

The Conservation Commission signed the application but did not submit comments.

APPROVE PERMIT:

Temporary impact of 318 square feet of an intermittent stream (20 linear feet along the channel centerline) and associated forested wetlands to install two sewer lines to a condominium complex.

With Conditions:

1. All work shall be in accordance with plans by Arthur F. Siciliano Jr. dated December 2005, as received by the DES Wetlands Bureau on December 20, 2005.
2. This permit is contingent on approval by the DES Subsurface Systems Bureau.
3. This permit is contingent on approval by the DES Site Specific Bureau.
4. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).
5. Any future work on this property that is within the jurisdiction of the DES Wetlands Bureau as specified in RSA 482-A will require a new application and approval by the Bureau.
6. All work shall be done during low flow.
7. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized.
8. Appropriate turbidity controls shall be installed prior to construction, shall be maintained during construction such that no turbidity escapes the immediate dredge area, and shall remain until suspended particles have settled and the water at the work site has returned to normal clarity.
9. Silt fence(s) must be removed once the area is stabilized.
10. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
11. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
12. Area shall be regraded to original contours following completion of work.
13. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
14. Wetland replication area shall have at least 75% successful establishment of wetlands vegetation after two (2) growing seasons, or it shall be replanted and re-established until a functional wetland is replicated in a manner satisfactory to the DES Wetlands Bureau.
15. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid prior to entering surface waters or wetlands.
16. Faulty equipment shall be repaired prior to entering jurisdictional areas.
17. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
18. All refueling of equipment shall occur outside of surface waters or wetlands during construction.
19. Additional expedited minimum impact applications shall be accepted for the subject property for a period of 12 months only if the applicant demonstrates by plan that the additional project(s) are wholly unrelated or separate from the original application and when considered with the original application are not classified as minor or major.

With Findings:

1. This is a minimum impact project per Administrative Rule Wt 303.04(i), construction of temporary crossings of brooks, streams, or rivers for the transportation of forest products or the construction or maintenance of utility pipes or lines and is not in prime wetlands or within 100 feet of the highest observable tide line or does not meet the requirements of Wt 303.02(k).
2. The need for the proposed impacts has been demonstrated by the applicant per Wt 302.01. The temporary impacts are necessary for the installation of two sewer lines between the condominium units and leach field.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the DES Wetlands Bureau's jurisdiction per Wt 302.03. The proposed sewer lines cross the wetlands at the narrowest point in relation to the leach field.
4. The applicant has demonstrated by plan and example that each factor listed in Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.
5. Other wetland impacts associated with the condominium development were permitted by the DES Wetlands Bureau on November 4, 1986 (permit #F-674) and September 9, 1987 (permit #E-340). The applicant has stated that all work previously permitted was completed per the conditions and within the allotted time period of these permits.

6. The applicant's agent has stated that the project will not need any other wetland disturbance to finish construction.
7. The Nongame and Endangered Wildlife Program of the NH Fish and Game Department did not have record of any rare or endangered species near the project area.

2006-00548 SICILIANO, ARTHUR & YVONNE
WEARE Unnamed Wetland

Requested Action:

Dredge and fill 1,145 square feet of palustrine forested wetlands for construction of an access road and turnaround for a 9-lot residential subdivision on an approximately 27 acre parcel with approximately 14 acres of open space.

Conservation Commission/Staff Comments:

The Conservation Commission signed the application but did not submit comments.

APPROVE PERMIT:

Dredge and fill 1,145 square feet of palustrine forested wetlands for construction of an access road and turnaround for a 9-lot residential subdivision on an approximately 27 acre parcel with approximately 14 acres of open space.

With Conditions:

1. All work shall be in accordance with plans by Arthur F. Siciliano, dated January 2006 (revised), as received by the DES Wetlands Bureau on March 14, 2006.
2. This permit is contingent on approval by the DES Subsurface Systems Bureau.
3. This permit shall not be effective until it has been recorded with the County Registry of Deeds by the Permittee and a copy of the registered permit has been received by the DES Wetlands Bureau.
4. The deed which accompanies the sales transaction of each lot in this subdivision shall contain condition #5 of this approval.
5. There shall be no further alteration of wetlands for lot development, driveways, culverts, or for septic setback.
6. All work shall be done during low flow.
7. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
8. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
9. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August 1992).
10. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
11. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
12. Orange construction fencing shall be placed at the limits of construction adjacent to the wetland impact area to prevent accidental encroachment on wetlands.
13. Construction equipment shall be inspected daily for leaking fuel, oil, and hydraulic fluid prior to entering surface waters or wetlands.
14. Faulty equipment shall be repaired prior to entering jurisdictional areas.
15. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
16. All refueling of equipment shall occur outside of surface waters or wetlands during construction.
17. Additional expedited minimum impact applications shall be accepted for the subject property for a period of 12 months only if the applicant demonstrates by plan that the additional project(s) are wholly unrelated or separate from the original application and when considered with the original application are not classified as minor or major.

With Findings:

1. This is a minimum impact project per Administrative Rule Wt 303.04 (f), projects involving alteration of less than 3,000 square feet in swamps or wet meadows that are not in prime wetlands or do not meet the requirements of Wt 303.02(k), provided that no previous department permit has placed restrictions on the property of the applicant.
2. The need for the proposed impacts has been demonstrated by the applicant per Wt 302.01. The impacts are necessary for the construction of an access road and turnaround for a 9-lot residential subdivision.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the DES Wetlands Bureau's jurisdiction per Wt 302.03. The access road was configured to follow an existing driveway and the turnaround was located as far east as possible to minimize wetlands impacts.
4. The applicant has demonstrated by plan and example that each factor listed in Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.
5. The proposed subdivision consists of eight (8) buildable lots approximately 13 acres in total area and one (1) open space lot approximately 14 acres in area.
6. The Conservation Commission signed the application but did not submit comments.
7. The proposed impacts occur within one-quarter mile of the Piscataquog River, a Designated River protected under RSA 483. The Local Advisory Committee was notified of the project on March 27, 2006 but did not comment within the comment period.
8. The Nongame and Endangered Wildlife Program of the NH Fish and Game Department did not have record of any rare or endangered species near the project area.
9. This permit is contingent on approval by the DES Subsurface Systems Bureau.

GOLD DREDGE

2006-00743 SICELY, SANDRA
(ALL TOWNS) Unnamed Stream

Conservation Commission/Staff Comments:
cc: Bath Con Comm

APPROVE PERMIT:
Gold Dredge

2006-00745 SICELY, JOSEPH
(ALL TOWNS) Unnamed Stream

Conservation Commission/Staff Comments:
cc: Bath Con Comm

APPROVE PERMIT:
Gold Dredge

LAKES-SEASONAL DOCK NOTIF

2005-01190 JONES, KEVIN
GILFORD Lake Winnepesaukee

Requested Action:

Install a seasonal dock

PBN DISQUALIFIED:

Install a seasonal dock

With Findings:

1. Seasonal dock notification disqualified as this is not the only docking structure on the frontage.

2006-00701 MORRISSETTE, LISA
LACONIA Winnisquam Lake

COMPLETE NOTIFICATION:

Laconia Tax Map#382 Lot#199-9 Winnisquam Lake

2006-00702 TOBIN, JAMES
SANBORNVILLE Great East Lake

COMPLETE NOTIFICATION:

Sanbornville Tax Map#24 Lot#94 Great East Lake

2006-00703 RAYMOND, RICHARD / CAROL
WOLFEBORO Crescent Lake

COMPLETE NOTIFICATION:

Wolfeboro Tax Map#10 Lot#28 Block#7
Crescent Lake

2006-00719 GODIN, RICHARD
RINDGE Monomonac Lake

COMPLETE NOTIFICATION:

Rindge Tax Map# 14 Lot# 54 Monomonac Lake

2006-00727 BEATTIE, WILLIAM
LEBANON Mascoma Lake

COMPLETE NOTIFICATION:

Lebanon Tax Map# 98 Lot# 6 Mascoma Lake

2006-00736 BIXBY, BENJAMIN / ELIZABETH
KINGSTON Kingston Lake

COMPLETE NOTIFICATION:

Kingston Tax Map#60 Lot#000020 Kingston Lake

SHORELAND VARIANCE / WAIV

2006-00148 MCCARRON, THOMAS
BELMONT Silver Lake

Requested Action:

Increase the nonconforming primary structure's setback from 6.21 feet to 7.71 feet from the reference line, increase the ridgeline height from 19 feet to 28 feet, increase the footprint within the primary building setback from 660 square feet to 1321 square feet.

Inspection Date: 02/16/2006 by Heather S Dionne

APPROVE CSPA WAIVER:

Increase the nonconforming primary structure's setback from 6.21 feet to 7.71 feet from the reference line, increase the ridgeline height from 19 feet to 28 feet, increase the footprint within the primary building setback from 660 square feet to 1321 square feet.

With Conditions:

1. All work shall be conducted in accordance with plans as received by the department on January 26, 2006 and March 1, 2006.
2. This approval shall not be effective until it has been recorded at the appropriate County Registry of Deeds and a copy of the recorded waiver is sent to the department.
3. Unnecessary removal of vegetation within the shoreland during construction shall be prohibited.
4. All planted vegetation shall be native and consistent with surrounding natural vegetation on the property and surrounding properties. Planting invasive or exotic species is strictly prohibited.
5. This approval does not allow lakeward expansion of the primary structure.
6. The applicant shall construct a crawl space under the structure at the top of the 100-year flood mark, as well as construct a retaining wall to raise the grade to reduce contamination during a flooding event.
7. No open deck or porch constructed shall extend more than 12 feet towards the reference line.
8. The contractor/owner responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).
9. A copy of this waiver shall be posted on site during construction in a prominent location visible to inspecting personnel.
10. This waiver does not exempt the owner from obtaining any other necessary local, state or federal permits or approvals.
11. The owner shall maintain compliance with all other requirements of the Comprehensive Shoreland Protection Act, RSA 483-B.

With Findings:

1. The existing non-conforming residence is located within the 50 foot primary building setback to Silver Lake and therefore fails to conform to the setback restriction set forth in RSA 483-B:9, II, of the CSPA.
2. In accordance with RSA 483-B:11, II, the commissioner shall review proposals which are more nearly conforming than the existing structures, and may waive some of the standards specified in RSA 483-B:9, so long as there is at least the same degree of protection provided to the public waters and the proposal is "more nearly conforming." More nearly conforming "means a proposal for significant changes to the location or size of the existing structures that bring the structures into greater conformity, or a proposal for changes to other aspects of the property, including but not limited to stormwater management, wastewater treatment or traffic volume or flow, or both types of proposal which significantly improve wildlife habitat or resource protection."
3. The applicant has proposed to increase the distance between the structure to the reference line and therefore meets the requirements for a waiver to RSA 483-B:9 as described in RSA 483-B: 11, II.

ROADWAY MAINTENANCE NOTIF

2006-00628 NH DEPT OF TRANSPORTATION
SULLIVAN Unnamed Stream

PERMIT BY NOTIFICATION

2006-00614 BEAUBOEUF, ANDRE & NICOLE BOUCHER
SANDWICH Unnamed Wetland

2006-00676 HI SPOT CONDOMINIUM ASSOCIATION
LACONIA Paugus Bay

Requested Action:

Remove rock, repair/replace 110.5 ft of retaining wall that is lakeward of normal high water.

PBN DISQUALIFIED:

Remove rock, repair/replace 110.5 ft of retaining wall that is lakeward of normal high water.

With Findings:

1. This project is disqualified from the PBN process because it does not meet the criteria under 303.04 (c) Repair or replacement of existing retaining walls that is performed "in the dry".
2. There is no indication when the work is to take place. Photos indicate that the work will not take place in the dry. Photos show lake elevation down more than 1.5 ft, yet wall is still under water.

2006-00684 FLYWAY FARM, LLC
TEMPLE Unnamed Pond

Requested Action:

Temporary impact of 74 square feet in the bank and bed of a pond for installation of a dry hydrant.

Conservation Commission/Staff Comments:

The Conservation Commission signed the PBN but did not submit comments.

PBN IS COMPLETE:

Temporary impact of 74 square feet in the bank and bed of a pond for installation of a dry hydrant.

With Findings:

1. This is a minimum impact project per Administrative Rule Wt 303.04(w), excavation of less than 10 linear feet within the bank and bed of a surface water that does not exceed 200 square feet in total jurisdictional impact to the bed, for installation of a dry hydrant.

2006-00706 WISE, DOUGLAS & JOANNE
LYME Unnamed Pond

Requested Action:

Dredge and fill approximately 200 square feet of pond bed and bank for installation of dry hydrant, per request of Lyme Fire Department.

PBN IS COMPLETE:

Dredge and fill approximately 200 square feet of pond bed and bank for installation of dry hydrant, per request of Lyme Fire Department.

2006-00707 JOHNSON, RUSSEL
WASHINGTON Highland Lake

Requested Action:

Replenish existing beach

With Findings:

1. This is a minimum impact project per Administrative Rule Wt 303.04(aa) replenishment of a beach.

2006-00725 NH DEPT OF TRANSPORTATION
ANDOVER Bradley Brook

PBN IS COMPLETE:

Construct new bridge seats and bridge deck with staging to be placed beneath the bridge and additional stone to be installed behind existing wing walls for stabilization.