

Wetlands Bureau Decision Report

Decisions Taken
10/17/2006 to 10/22/2006

DISCLAIMER:

This document is published for information purposes only and does not constitute an authorization to conduct work. Work in jurisdiction may not commence until the applicant has received a posting permit.

Decisions are subject to appeal, and are reviewed by the federal agencies for compliance with Section 404 of the Federal Clean Water Act.

APPEAL:

I. Any affected party may ask for reconsideration of a permit decision in accordance with RSA 482-A:10,II within 20 days of the Department's issuance of a decision. Requests for reconsideration should:

- 1) describe in detail each ground for complaint. Only grounds set forth in the request for reconsideration can be considered at subsequent levels of appeal;
- 2) provide new evidence or information to support the requested action;
- 3) Parties other than the applicant, the town, or contiguous abutters must explain why they believe they are affected; and
- 4) Be mailed to the DES Wetlands Bureau, PO Box 95, Concord, NH 03302-0095.

II. An appeal of a decision of the department after reconsideration may be filed with the Wetlands Council in accordance with RSA 482-A:10, IV within 30 days of the department's decision. Filing of the appeal must:

- 1) be made by certified mail to Brian Fowler, Chairperson, Wetlands Council, PO Box 95, Concord, NH 03302-0095 (a copy should also be sent to the DES Wetlands Bureau);
- 2) contain a detailed description of the land involved in the department's decision; and
- 3) set forth every ground upon which it is claimed that the department's decision is unlawful or unreasonable.

MAJOR IMPACT PROJECT

**2005-02562 BLYE HILL LANDING HOMEOWNERS ASSOCIATION
NEWBURY Lake Sunapee**

Requested Action:

Request to reconfigure approved docking facility to increase distance from piers to south property line.

Conservation Commission/Staff Comments:

No Con Com comments by Jan 5, 2006

Inspection Date: 02/01/2006 by Jeffrey D Blecharczyk

APPROVE AMENDMENT:

Amend permit to read: Permanently remove an existing 6 ft by 44 ft permanent walkway over public waters, permanently remove an existing 4 ft by 30 seasonal dock, relocate 6 rocks posing hazard to navigation and construct three 6 ft by 24 ft permanent piling docks connected by a 6 ft by 60 ft permanent walkway in a "W" configuration, install four, 3 piling ice clusters, and install 9 tie off piles, on an average of 382 ft of frontage on Lake Sunapee, Newbury.

With Conditions:

1. All work shall be in accordance with plans by Watermark Marine Construction revised September 13, 2006, as received by the Department on October 16, 2006.
2. This permit shall not be effective until it has been recorded with the Registry of Deeds Office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to construction.
3. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
4. Construction debris shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
5. The existing 6 ft by 44 ft walkway over public waters shall be completely removed prior to the construction of the new docking facility.
6. Repairs to these structures may be conducted, as necessary, throughout the duration of this permit provided that the Permittee notifies the Wetlands Bureau and Conservation Commission, in writing, of the proposed start and completion date prior to performing any repair.
7. Repairs shall maintain existing size, location and configuration.
8. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, maintained during construction, and shall remain until the area is stabilized.
9. This permit does not allow for maintenance dredging.
10. The dock shall not extend more than 30 ft lakeward at full lake elevation of 1094.15.
11. The minimum clear spacing between piles shall be 12 feet.
12. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This project is classified as a major project per Rule Wt 303.02(d), construction of a major docking facility.
2. The applicant has an average of 382 feet of frontage along Lake Sunapee.
3. A maximum of 6 slips may be permitted on this frontage per Rule Wt 402.12, Frontage Over 75'.
4. The proposed docking facility will provide 6 slips as defined per RSA 482-A:2, VIII and therefore meets Rule Wt 402.12.
5. The total sq ft surface area of the existing and proposed structures over public submerged lands will not exceed the sq ft of surface area of new conforming structures which could be approved on the lot therefore Rule Wt 402.20, Modification of existing structures is waived.
6. Public hearing is waived based on field inspection, by NH DES staff, on February 1, 2006, with the finding that the project impacts will not significantly impair the resources of Lake Sunapee.
7. The modification of the docking facility as proposed increases the setback to the south property line by 27 ft.

-Send to Governor and Executive Council-

MINOR IMPACT PROJECT

2005-00978 TERRA FIRMA REAL ESTATE LLC, JOHN GAGNON
LONDONDERRY Unnamed Wetland

Requested Action:

Dredge and fill approximately 8,660 sq. ft. of wetlands for access to a proposed 5-lot subdivision.

WITHDRAW APPLICATION:

The proposed project has been redesigned and the applicant submitted a new minimum expedited application and requested the current application be withdrawn.

2005-02177 GOFFSTOWN PUBLIC WORKS, TOWN OF
GOFFSTOWN Harry Brook

Requested Action:

Amendment request to add an approximately 60 linear foot retaining wall (no additional wetlands impact) to the bridge design, change bridge structure from an arch span to a square box culvert design, reduce Japanese knotweed removal/restoration to 380 sq. ft. of temporary impact, and include 435 sq. ft. of impact resulting from emergency repair of the existing bridge repair (Wetlands Bureau Emergency Authorization File # 2006-1144).

APPROVE AMENDMENT:

Dredge and fill approximately 3,405 square feet (consisting of 2,205 square feet of temporary impact and 1,200 square feet of permanent impact) of riverine, palustrine forested, scrub-shrub and emergent wetlands within and adjacent to Harry Brook. Work within jurisdiction consists of removing the existing approximately 7 foot x 19 foot x 26 foot span jack arch bridge and bridge abutments and associated sediment and replacing with an approximately 8 foot x 19 foot x 33 foot pre-cast box culvert bridge, footings, wing walls, restoration of the stream bed and adjacent wetlands and restoration of adjacent wetlands dominated by Japanese knotweed and construction of a new vegetated treatment swale.

With Conditions:

1. All work shall be in accordance with plans and narratives prepared by the Town of Goffstown, Department of Public Works, Proposed Treatment Swale plan sheet, dated December 19, 2005, as received by the Department on December 29, 2005 and plan sheet 1 of 1 Erosion Control Detail, revision dated February 10, 2006, as received by the Department on February 21, 2006, plan sheet 1 of 1 Proposed Bridge Details, revision dated June 21, 2006, plan sheet 1 of 1 Japanese Knotweed Additional Temporary Wetland Impact, revision dated July 28, 2006 as received by the Department on August 4, 2006, narratives as received by the Department on September 14, 2005, revised narratives, dated December 23, 2005, as received by the Department on December 29, 2005 and revised narrative, dated July 28, 2006 as received by the Department on August 4, 2006.
2. This permit is contingent on the Town of Goffstown obtaining construction easements from affected landowners outside of the existing road right-of-way. The Town shall supply copies of the recorded easements to DES Wetlands File No. 2005-02177 prior to the start of construction.
3. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
4. Work shall be done during low flow conditions.

5. This permit is contingent on review and approval, by the DES Wetlands Bureau, of final stream diversion/erosion control plans. Those plans shall detail the timing and method of stream flow diversion during construction, and show temporary siltation/erosion/turbidity control measures to be implemented.
6. The Permittee shall monitor the weather and will not commence work within flowing water, including the installation of cofferdams, when rain is in the forecast.
7. All in-stream work shall be conducted in a manner that minimizes the duration of construction in the watercourse. In-stream work shall not exceed five consecutive days in total unless specifically authorized in writing by the Wetlands Bureau.
8. There shall be no excavation or operation of construction equipment in flowing water.
9. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
10. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
11. Any native material removed from the streambed for installation of the new bridge footings shall be stockpiled separately and reused to emulate a natural channel bottom. Any new materials used within the stream channel must be similar to the natural stream substrate and shall not include angular rip-rap.
12. Temporary wetland impact areas shall be regraded to original contours.
13. Wetland restoration areas shall have at least 75% successful establishment of wetlands vegetation after two (2) growing seasons, or it shall be replanted and re-established until a functional wetland is replicated in a manner satisfactory to the DES Wetlands Bureau.
14. Follow-up monitoring reports shall be submitted to DES within 60-days following completion of the project and at the end of two consecutive growing season following the completion of the project. The reports shall include narratives and photographs describing the status of the wetland restoration areas. The reports shall be prepared by a qualified professional.
15. Any areas from which vegetation has been cleared to gain access to the site shall be replanted with native species.
16. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid prior to entering surface waters or wetlands. Faulty equipment shall be repaired prior to entering jurisdictional areas.
17. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
18. All refueling of equipment shall occur outside of surface waters or wetlands during construction.

With Findings:

1. This is a minor impact project per Administrative Rule Wt 303.03(1); projects that alter the course of or disturb less than 200 linear feet of an intermittent or perennial nontidal stream or river channel or its banks and do not meet the criteria for minimum impact under Wt 303.04(n).
2. The need for the proposed impacts has been demonstrated by the applicant per Wt 302.01.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.
5. The New Hampshire Fish and Game Department (NHFGD) identified that their records show the brook floater (*Alasmidonta varicose*) and bridled shiner (*Notropis bifrenatus*) occur near the project site. NHFGD stated that they do not expect any impacts to these species by the project if an appropriately sized bottomless culvert is used and appropriate sediment controls be installed during construction and maintained until all soils are stabilized.
6. The proposed replacement bridge is approximately the same size as the existing bridge and is an open bottom structure.
7. The permit is contingent on appropriate erosions, sediment and turbidity controls.
8. The project includes construction of a new stormwater treatment swale that will improve the quality of the current stormwater runoff entering Harry Brook.
9. The Piscataquog River Local Advisory Committee (PRLAC) submitted comments suggesting that the crossing must be at least bankfull width to avoid future impacts to adjacent wetlands, timing of the work must be between July 1 and September 15 to protect spawning and larval life stages of fish species and that herbicide used to control Japanese knotweed on the site must be prevented from entering adjacent wetlands.
10. The proposed bridge is approximately the same size as the existing bridge.
11. The proposed bridge construction will take place in the month of August.

12. The revised restoration plan for the Japanese knotweed areas will not use herbicide and proposes removal of the knotweed by hand and replanting with native plant species.
13. The proposed amendment is not a substantial design change and addresses the follow-up requirements to emergency authorization #2006-1144.

2005-02926 CLARK, ROSALIE
MOULTONBOROUGH Lake Winnepesaukee

Requested Action:

Remove existing timbers on shoreline, replace with rock, and add native plantings along 70 linear ft of bank property having 430 feet of frontage on Lake Winnepesaukee, Moultonborough.

Conservation Commission/Staff Comments:

No comments from the local Con Com by 2/22/06
NH Fish and Game and NH NHI will not be submitting comments

APPROVE PERMIT:

Remove existing timbers on shoreline, replace with rock, and add native plantings along 70 linear ft of bank property having 430 feet of frontage on Lake Winnepesaukee, Moultonborough.

With Conditions:

1. All work shall be in accordance with plans by Stephanie Sanford, dated September 19, 2006, as received by the Department on September 20, 2006.
2. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
3. Dredged material and construction debris shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
4. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
5. Unnecessary removal of vegetation within the shoreland during construction shall be prohibited.
6. All planted vegetation shall be native and consistent with surrounding natural vegetation on the property and surrounding properties. Planting invasive or exotic species is strictly prohibited.
7. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minor impact project per Administrative Rule Wt 303.03(k), projects that disturb between 50 and 200 ft along the shoreline.

2006-00165 WALPOLE, TOWN OF
KEENE Great Brook

Requested Action:

Dredge and fill 2,123 square feet (489 square feet permanent impacts) in the banks of a perennial stream (impacting 182 linear feet) to replace an existing bridge with a 32-foot span pre-cast concrete bridge structure, including the installation of new abutments and wingwalls and rip-rap protection, and make associated road improvements on a public roadway.

APPROVE PERMIT:

Dredge and fill 2,123 square feet (489 square feet permanent impacts) in the banks of a perennial stream (impacting 182 linear feet) to replace an existing bridge with a 32-foot span pre-cast concrete bridge structure, including the installation of new abutments and wingwalls and rip-rap protection, and make associated road improvements on a public roadway.

With Conditions:

1. All work shall be in accordance with plans by SEA Consultants Inc. dated June 2005 and January 2006 as received by the DES Wetlands Bureau on September 19, 2006.
2. Any future work at this site that is within the jurisdiction of the DES Wetlands Bureau as specified in RSA 482-A will require a new application and approval by the Bureau.
3. All work shall be done during low flow.
4. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain until the area is stabilized.
5. Appropriate turbidity controls shall be installed prior to construction, shall be maintained during construction such that no turbidity escapes the immediate dredge area, and shall remain until suspended particles have settled and the water at the work site has returned to normal clarity.
6. Erosion control structures shall be removed once the area is stabilized.
7. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).
8. Excavation work shall not start within the stream banks until the flow of the stream is diverted in accordance with the approved plans.
9. All excavation work shall be done in the dry, including stockpiling of temporarily excavated materials, and at no time shall any construction equipment work within the flow of the stream.
10. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
11. Dredged material shall be dewatered in sedimentation basins located outside of the jurisdiction of the DES Wetlands Bureau. The dewatering area shall be lined with siltation and erosion controls to prevent runoff from entering jurisdictional areas.
12. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
13. Temporary structures installed to channel flow through the work area during construction shall be entirely removed immediately following construction.
14. Temporarily impacted areas shall be restored to their original grades and to a stable condition within three days of completion of construction.
15. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
16. Construction shall be inspected by a certified wetland scientist, erosion control specialist, or professional engineer to ensure that appropriate protective measures are properly implemented, including those outlined in the plans and documents supporting this permit application and the conditions of this authorization.
17. Extreme caution should to be taken to limit unnecessary removal of vegetation from riparian areas.
18. Areas from which vegetation has been cleared shall be replanted with similar native (noninvasive) species.
19. Restoration of temporary impact areas shall have at least 75% successful establishment of wetlands vegetation after two (2) growing seasons, or they shall be replanted and re-established until a functional wetland is replicated in a manner satisfactory to the DES Wetlands Bureau.
20. Restoration shall not be considered successful if sites are newly invaded by nuisance species such as common reed or purple loosestrife during the first full growing season following project completion. The applicant shall work with the DES Wetlands Bureau to attempt to eradicate nuisance species newly found during this same period.
21. Orange construction fencing shall be placed at the limits of construction to prevent accidental encroachment on jurisdictional areas.
22. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid prior to entering or working near surface waters or wetlands.
23. Faulty equipment shall be repaired prior to entering or working near jurisdictional areas.
24. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
25. All refueling of equipment shall occur outside of surface waters or wetlands during construction.

With Findings:

1. This is a minor impact project per Administrative Rule Env-Wt 303.03(l), projects that alter the course of or disturb less than

200 linear feet of an intermittent or perennial nontidal stream or river channel or its banks and do not meet the criteria for minimum impact under Env-Wt 303.04(n). For perennial streams or rivers, the total disturbance shall be calculated by summing the lengths of disturbances to the channel and the banks.

2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the DES Wetlands Bureau's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.
5. The most recent NH Department of Transportation inspection report completed in 2001 indicates that the original bridge was built in 1927 and has not been rebuilt. The overall poor condition of the bridge warrants a complete replacement of the structure.
6. The project will impact Great Brook which outlets to the Connecticut River approximately 1.5 miles downstream of the project site.
7. The proposed structure will have the same hydraulic opening as the existing structure.
8. The applicant submitted "Easement Letters of Understanding" signed by the owners of abutting properties for work outside of the Right-Of-Way.
9. Impacts to plant communities identified by the NH Natural Heritage Bureau are not anticipated as a result of the proposed project.
10. The Nongame and Endangered Wildlife Program of the NH Fish and Game Department did not have record of any rare or endangered species near the project area.

2006-00412 SNYDER, ELSIE
BEDFORD Unnamed Wetland

Requested Action:

Dredge and fill approximately 7,880 sq. ft. of forested wetlands to construct a driveway to one lot of a two lot residential subdivision.

APPROVE PERMIT:

Dredge and fill 5,725 sq. ft. of forested wetlands to construct a driveway to one lot of a two lot residential subdivision. Work in wetlands includes installation of two crossings within one access road consisting of the following: Wetland Impact-1, 2,100 sq. ft. of wetlands impact consisting of the installation of (2) 18 in. x 18 ft. HDPE culverts, headwall, rip rap outlet protection and associated grading, Wetland Impact-2, 3,625 sq. ft. of wetlands impact consisting of the installation of (1) 18 in. x 20 ft. HDPE culvert, headwall, rip rap outlet protection and associated grading.

With Conditions:

1. All work shall be in accordance with plans by Eric Mitchell & Associates, Inc., dated August 20, 2006, as received by the Department on September 11, 2006.
2. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
3. This permit is contingent on approval by the DES Subsurface Systems Bureau.
4. There shall be no further alteration of wetlands for lot development, driveways, culverts, or for septic setback.
5. The deed which accompanies the sales transaction for each of the lots in this subdivision shall contain condition #4 of this approval.
6. This permit shall not be effective until it has been recorded with the County Registry of Deeds office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to construction.
7. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
8. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
9. Orange construction fencing shall be placed at the limits of construction adjacent to wetlands to prevent accidental encroachment.
10. Within three days of final grading in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be

stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.

11. Where construction activities have been temporarily suspended within the growing season, all exposed soil areas shall be stabilized within 14 days by seeding and mulching.
12. Where construction activities have been temporarily suspended outside the growing season, all exposed areas shall be stabilized within 14 days by mulching and tack. Slopes steeper than 3:1 shall be stabilized by matting and pinning.
13. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).
14. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid. Faulty equipment shall be repaired immediately.
15. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
16. All refueling of equipment shall occur outside of surface waters or wetlands during construction.

With Findings:

1. This is a minor impact project per Administrative Rule Env-Wt 303.03(h), projects involving less than 20,000 square feet of alteration in the aggregate in nontidal wetlands, nontidal surface waters, or banks adjacent to nontidal surface waters which exceed the criteria of Env-Wt 303.04 (f).
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.
5. The applicant provided a wetland delineation plan ("Wetland Impact & Concept Plan", dated February 21, 2006, revision dated May 11, 2006) stamped by a New Hampshire Certified Wetlands Scientist ("CWS") and a Professional Engineer in accordance with Administrative Rule Env-Wt 304.09(a).
6. The CWS submitted wetland delineation data sheets to confirm the new wetland delineation boundary.
7. The Conservation Commission voted not to recommend approval of the original design impacting 7,880 square feet of wetlands.
8. The Conservation Commission voted to recommend approval of the revised design impacting 5,950 square feet of wetlands.
9. The revised impact design has been further reduced to 5,725 square feet of wetlands impact.
10. The New Hampshire Fish & Game Department did not submit comments.

2006-00520 LANG, DAVID/NICOLE
MEREDITH Lake Winisquam

Requested Action:

Stabilize 100 linear ft of bank with a 3 ft wide retaining wall and vegetatively stabilize soils behind wall on 100 ft of frontage on Winnisquam Lake in Meredith.

APPROVE PERMIT:

Stabilize 100 linear ft of bank with a 3 ft wide retaining wall and vegetatively stabilize soils behind wall on 100 ft of frontage on Winnisquam Lake in Meredith.

With Conditions:

1. All work shall be in accordance with plans by David and Nichole Lang dated October 10, 2006, as received by the Department on October 11, 2006.
2. Retaining wall shall be constructed for the stabilization of the existing bank. Retaining wall shall not be lakward of the normal high water mark elevation.
3. The new wall shall be maintained such that the structure shall conform to reasonable safety standards. Failure to maintain a structure in a safe condition shall be considered a violation as per Administrative Rule Env-Wt 402.10.
4. Wall shall not reflect or re-direct currents towards adjacent wetlands or structures, or otherwise contribute to erosion.

5. Work authorized shall be carried out such that discharges shall be avoided in spawning or nursery areas during spawning seasons, and impacts to such areas shall be avoided or minimized to the maximum extent practicable during all times of the year.
6. Work shall be carried out in a time and manner such that disturbance to migratory waterfowl breeding and nesting areas shall be avoided.
7. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
8. Within 8 months of the issuance of this permit the Landowner shall submit to the Department a written report by a professional engineer documenting the effectiveness newly constructed retaining wall and recommending any modifications necessary to prevent further bank degradation.
9. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minor impact project per Administrative Rule Env-Wt 303.03(k), projects tht disturb between 50 and 200 linear feet, measured along the shoreline, of a lake or pond or its bank and do not meet the criteria of Wt 303.02.
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01. 3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.

**2006-00521 PIPING ROCK LAND OWNERS ASSOCIATION, RICHARD HEIDE
WOLFEBORO Lake Winnepesaukee**

Requested Action:

Permanently remove a non-conforming crib and seasonal docking structure and construct a 4 ft by 25 ft seasonal dock attached to a 4 ft by 41 ft seasonal dock in a "T" configuration anchored by a 4 ft by 5 ft concrete pad, and add 9 cubic yards of sand to 150 sq ft of existing beach on Lake Winnepesaukee, Wolfeboro.

Conservation Commission/Staff Comments:

Con Com recommends not adding sand until beach is perched since erosion from the beach is the reason it is shallow, and questions whether the 45 ft dock on 70 ft of frontage is acceptable.

APPROVE PERMIT:

Permanently remove a non-conforming crib and seasonal docking structure and construct a 4 ft by 25 ft seasonal dock attached to a 4 ft by 41 ft seasonal dock in a "T" configuration anchored by a 4 ft by 5 ft concrete pad, and add 9 cubic yards of sand to 150 sq ft of existing beach on Lake Winnepesaukee, Wolfeboro.

With Conditions:

1. All work shall be in accordance with plans by Watermark Marine Construction dated January 12, 2006, as received by the Department on March 10, 2006.
2. This permit shall not be effective until it has been recorded with the Registry of Deeds Office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to installation.
3. This shall be the only structure on this water frontage and all portions of the dock shall be at least 20 ft from abutting property lines or the imaginary extension of those lines into the water.
4. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
5. Construction debris shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
6. The existing dock shall be completely removed prior to the construction of the approved dock.
7. Seasonal pier shall be removed from the lake for the non-boating season.
8. No portion of the pier shall extend more than 45 feet from the shoreline at full lake elevation.
9. No more than 9 cu yd of sand may be used and all sand shall be located above the normal high water line.

10. This permit shall be used only once, and does not allow for annual beach replenishment.
11. The permittee shall provide appropriate diversion of surface water runoff to prevent erosion of beach area.
12. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and shall remain until the area is stabilized.
13. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minor impact project per Administrative Rule Env-Wt 303.03(d), construction of a docking system that exceeds Env-Wt 402.01 for minimum impact docks classified under Env-Wt 303.04.
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01. 3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.
5. The applicant has an average of 70 feet of shoreline frontage along Lake Winnepesaukee.
6. The proposed docking facility will provide 1 slip as defined per RSA 482-A:2, VIII and therefore meets Rule Env-Wt 402.12.
7. The site does not have a history of beach replenishment which would contribute to the shallowness of the cove.

2006-00766 ARROW EQUIPMENT INC
LITTLETON Unnamed Wetland

Requested Action:

Dredge and fill approximately 4,000 square feet of forested wetlands and approximately 50 linear feet of intermittent stream for access to a 7-lot subdivision on 21.28 acres.

APPROVE PERMIT:

Dredge and fill 2,990 square feet of forested wetlands and approximately 50 linear feet of intermittent stream for access to a 7-lot subdivision on 21.28 acres, further described as follows:

1. Retain 100 square feet of wetlands impact for road access;
2. Impact 1,800 square feet wetlands to install an 18-inch x 30-foot HDPE culvert for road access;
3. Impact 900 square feet of wetlands along approximately 50 linear feet of intermittent stream to install an 18-inch x 45-foot HDPE culvert for road access; and
4. Impact 190 square feet of wetlands to install an 18-inch x 20-foot HDPE culvert for driveway access to one (1) lot.

With Conditions:

1. All work shall be in accordance with plans by Associated Consulting Engineers dated July 09, 2006, as received by the Department on July 18, 2006, and revised plans as received by the Department on October 16, 2006.
2. This permit is contingent on approval by the DES Subsurface Systems Bureau.
3. There shall be no further alteration of wetlands for lot development, driveways, culverts, or for septic setback.
4. The deed which accompanies the sales transaction for each of the lots in this subdivision shall contain condition # 3 of this approval.
5. This permit shall not be effective until it has been recorded with the Registry of Deeds Office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau.
6. Work shall be done during low flow conditions.
7. Work shall be conducted in a manner so as to minimize turbidity and sedimentation.
8. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
9. Orange construction fencing shall be placed at the limits of construction within or directly adjacent to wetlands or surface waters.
10. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
11. Culverts shall be laid in alignment with the original flow path of surface waters and wetlands.
12. Culverts shall be laid at original grade.

13. Proper headwalls shall be constructed within seven days of culvert installation.
14. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).
15. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(f), alteration of less than 3,000 square feet of wetlands; and Env-Wt 303.04(n), alteration of less than 50 linear feet of an intermittent stream.
2. The Littleton Conservation Commission commented a culvert may be required at the existing roadway drainage way that will be impacted by the proposed site driveway entrance/exit or approach adjoining NH Route 135.
3. The applicant obtained a NHDOT driveway permit for a driveway entrance/exit or approach adjoining NH Route 135.
4. The site driveway entrance/exit is existing and was installed in the 1930's.
5. Fill associated with the site driveway entrance/exit is 40-feet from the abutting property line.
6. No comments were submitted from the NHFG Nongame and Endangered Wildlife Program or the Natural Heritage Bureau.
7. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01. 8. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
9. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.

2006-01271 CASE, ALEXANDER
NORTH HAMPTON Little River

Requested Action:

Impact 275 square feet within 30 linear feet of bank of the Little River for bank stabilization with rip rap on the road side slopes immediately adjacent to the bridge.

CONFIRM EMERGENCY AUTHORIZATION:

Impact 275 square feet within 30 linear feet of bank of the Little River for bank stabilization with rip rap on the road side slopes immediately adjacent to the bridge.

With Conditions:

1. Any future work on this property that is within the jurisdiction of the DES Wetlands Bureau as specified in RSA 482-A will require a new application and approval by the Bureau.

With Findings:

1. This project is classified as a minimum impact project per Rule Env-Wt 303.04 ((x) Maintenance, repair, or replacement of a nondocking structure such as a culvert, headwall, bridge, dam, residential utility line, or rip-rap slope of less than 50 linear feet.
2. The project was necessary to eliminate bank erosion from large storm events of the Little River for safe vehicular passage.
3. Emergency authorization for this work was issued by DES Wetlands Bureau Staff on May 31, 2006.
4. Review of the application submitted pursuant the emergency authorization indicates that work has been completed in accordance with the emergency authorization.

2006-01456 LODEWICK, PHILIP
SPOFFORD Lake Spofford

Requested Action:

Repair/Replace 50 linear ft of existing retaining wall on 45 ft of frontage on Spofford Lake in Spofford.

APPROVE PERMIT:

Repair/Replace 50 linear ft of existing retaining wall on 45 ft of frontage on Spofford Lake in Spofford.

With Conditions:

1. All work shall be in accordance with plans by Bob Riley dated October 10, 2006, as received by the Department on October 11, 2006.
2. Repair shall maintain existing size, location and configuration.
3. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
4. Work authorized shall be carried out such that discharges shall be avoided in spawning or nursery areas during spawning seasons, and impacts to such areas shall be avoided or minimized to the maximum extent practicable during all times of the year.
5. Work shall be carried out in a time and manner such that disturbance to migratory waterfowl breeding and nesting areas shall be avoided.
6. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
7. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
8. Dated photographic documentation of the replacement wall shall be submitted to the Wetlands Bureau as a notification of completion of the project.
9. Shall replacement wall fail within a 6 year period from date of completion, the landowner shall file a new application for retaining wall replacement with stamped plans prepared by a certified professional in erosion and sediment control and site may be subject to further stormwater evaluation and control.
10. The new replacement wall shall be maintained such that the structure shall conform to reasonable safety standards. Failure to maintain a structure in a safe condition shall be considered a violation as per Administrative Rule Env-Wt 402.10.
11. Wall shall not reflect or re-direct currents towards adjacent wetlands or structures, or otherwise contribute to erosion.
12. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minor impact project per Administrative Rule Env-Wt 303.03(j) Repair or replacement of existing retaining walls that requires work in the water.
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.

**2006-01777 OPEN DOORS CHRISTIAN FELLOWSHIP
LITCHFIELD Unnamed Wetland**

Requested Action:

Dredge and fill approximately 4,638 sq. ft. of previously disturbed wet meadow wetlands (agricultural field) for access to a proposed church. Work in wetlands includes installation of a 24 in. x 44 ft. HDPE culvert, headwalls and associated grading.

Conservation Commission/Staff Comments:

The Conservation Commission approved the proposed project with suggestions/comments.

APPROVE PERMIT:

Dredge and fill approximately 4,638 sq. ft. of previously disturbed wet meadow wetlands (agricultural field) for access to a proposed church. Work in wetlands includes installation of a 24 in. x 44 ft. HDPE culvert, headwalls and associated grading.

With Conditions:

1. All work shall be in accordance with plans by Keach-Nordstrom Associates, Inc., dated June 2006, as received by the Department on July 17, 2006.
2. This permit is contingent on approval by the DES Subsurface Systems Bureau.
3. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
4. Any future work on this property that is within the jurisdiction of the DES Wetlands Bureau as specified in RSA 482-A will require a new application and approval by the Bureau.
5. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
6. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
7. Orange construction fencing shall be placed at the limits of construction directly adjacent wetlands to prevent accidental encroachment.
8. Culvert outlets shall be protected in accordance with the DES Best Management Practices for Urban Stormwater Runoff Manual (January 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August 1992).
9. Within three days of final grading in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
10. Where construction activities have been temporarily suspended within the growing season, all exposed soil areas shall be stabilized within 14 days by seeding and mulching.
11. Where construction activities have been temporarily suspended outside the growing season, all exposed areas shall be stabilized within 14 days by mulching and tack. Slopes steeper than 3:1 shall be stabilized by matting and pinning.
12. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid. Faulty equipment shall be repaired immediately.
13. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.

With Findings:

1. This is a minor impact project per Administrative Rule Env-Wt 303.03(h), projects involving less than 20,000 square feet of alteration in the aggregate in nontidal wetlands, nontidal surface waters, or banks adjacent to nontidal surface waters which exceed the criteria of Env-Wt 303.04 (f).
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01. 3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.
5. The New Hampshire Fish & Game Department did not submit comments.
6. The Natural Heritage Bureau submitted comments regarding the identification of a State Endangered plant species, false pimpernel, identified near the project site. The species is supported by pond shore habitat.
7. The proposed wetlands impact is within a previously disturbed wet meadow (agricultural field) and does not impact pond shore habitat.

2006-01948 **MCDAVITT, KENNETH**
SANBORNVILLE **Lovell Lake**

Requested Action:

Repair/maintain 40 linear ft of rip-rapped shoreline, remove 60 sq ft of rock supporting fill under 6 ft x 16 ft permanent dock with a 6 ft 12 ft seasonal dock extension, and construct a 6 ft x 6 ft crib with existing fill, repair/replace existing stone lake access steps on 130 ft of frontage on Lovell Lake in Sanbornville.

APPROVE PERMIT:

Repair/maintain 40 linear ft of rip-rapped shoreline, remove 60 sq ft of rock supporting fill under 6 ft x 16 ft permanent dock with a 6 ft 12 ft seasonal dock extension, and construct a 6 ft x 6 ft crib with existing fill, repair/replace existing stone lake access steps on 130 ft of frontage on Lovell Lake in Sanbornville.

With Conditions:

1. All work shall be in accordance with plans by Kenneth McDavitt, as received by the Department on July 28, 2006.
2. This permit shall not be effective until it has been recorded with the appropriate county Registry of Deeds office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to construction.
3. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and shall remain until the area is stabilized.
4. Work shall be done during draw down or low flow.
5. Work shall be conducted in a manner so as to minimize turbidity and sedimentation to surface waters and wetlands.
6. Work shall be conducted in a manner that avoids excessive discharges of sediments to fish spawning areas.
7. Rip-rap shall be located landward of the shoreline at the normal high water, where practical, and shall not extend more than 2 feet lakeward of that line at any point.
8. Seasonal portion of the dock shall be removed for 5 months during the non-boating season.
9. The maximum size of cribs shall not exceed 6 feet long by 6 feet wide and of such height as necessary to support the docking structure above the water level. Variance to this condition may be sought if water depth is greater than 6 feet.
10. Crib material shall be timber, concrete, or other material approved by the Department of Environmental Services, and of such size and spacing as necessary to completely contain the ballast.
11. No more than one crib shall be installed for the support of the permanent portion of the dock.
12. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
13. These shall be the only structures on this water frontage and all portions of the dock shall be at least 20 ft from the abutting property lines or the imaginary extension of those lines into the water.
14. Access stairs shall be repaired "in-kind".
15. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minor impact project per Administrative Rule Env-Wt 303.03(d)(3), modification of a docking system that exceeds the design criteria as a minimum impact.
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(a) Requirements for Application Evaluation, has been considered in the design of the project.
5. Applicants proposal to remove 60 sq ft of excessive rock fill from under and around existing permanent portion of the dock and replace this support with a more conforming 6 ft x 6 ft crib and use the existing fill to repair and maintain the dilapidated rip-rapped shoreline is an favorable outcome to reduce existing impacts and restabilize area.

MINIMUM IMPACT PROJECT

**2006-01145 GOFFSTOWN, TOWN OF
GOFFSTOWN Hardy Brook**

Requested Action:

Emergency Authorization follow-up for after-the-fact approval to repair and replace an approximately 64 in. x 43 in. x 42 ft. CMP

culvert, granite headwalls and road surface that were destroyed by the spring of 2006 floods.

Conservation Commission/Staff Comments:

1. The Conservation Commission did not submit comments.
2. The New Hampshire Fish & Game Department did not submit comments.

CONFIRM EMERGENCY AUTHORIZATION:

Emergency Authorization follow-up for after-the-fact approval to repair and replace an approximately 64 in. x 43 in. x 42 ft. CMP culvert, granite headwalls and road surface that were destroyed by the spring of 2006 floods.

With Conditions:

1. Any further alteration of areas on this property that are within the jurisdiction of the DES Wetlands Bureau will require a new application and further permitting by the Bureau.

With Findings:

1. This project is classified as a Minimum impact project per Rule Env-Wt 303.04(x) Maintenance, repair or replacement of a nondocking structure such as a culvert, headwall, bridge, dam, residential utility line, or rip-rap slope of less than 50 linear feet.
2. The project was necessary to repair Montelona Road, provide safe access and stabilize the banks and bed of Hardy Brook.
3. Emergency authorization for this work was issued by DES Wetlands Bureau Staff on May 17, 2006.
4. DES Staff conducted a field inspection of the project site on May 17, 2006.
5. Review of the report submitted pursuant the emergency authorization indicates that work has been completed in accordance with the emergency authorization.
6. The repairs replaced an existing culvert and headwalls that were destroyed by the spring of 2006 flood events.

2006-01146

GOFFSTOWN, TOWN OF

GOFFSTOWN

Requested Action:

Emergency Authorization follow-up for after-the-fact maintenance and repair to remove sediment from a catch basin and drainage pipes and repair a ditchline within and adjacent to an intermittent stream impacted by the spring of 2006 floods.

Conservation Commission/Staff Comments:

1. The Conservation Commission did not submit comments.
2. The New Hampshire Fish & Game Department did not submit comments.

Inspection Date: 05/17/2006 by William A Thomas

CONFIRM EMERGENCY AUTHORIZATION:

Emergency Authorization follow-up for after-the-fact maintenance and repair to remove sediment from a catch basin and drainage pipes and repair a ditchline within and adjacent to an intermittent stream impacted by the spring of 2006 floods.

With Conditions:

1. Any further alteration of areas on this property that are within the jurisdiction of the DES Wetlands Bureau will require a new application and further permitting by the Bureau.

With Findings:

1. This project is classified as a Minimum impact project per Rule Env-Wt 303.04(x) Maintenance, repair or replacement of a nondocking structure such as a culvert, headwall, bridge, dam, residential utility line, or rip-rap slope of less than 50 linear feet.
2. The project was necessary to repair Tirrell Hill Road, provide safe access and stabilize an intermittent stream.

3. Emergency authorization for this work was issued by DES Wetlands Bureau Staff on May 17, 2006.
4. DES Staff conducted a field inspection of the project site on May 17, 2006.
5. Review of the report submitted pursuant the emergency authorization indicates that work has been completed in accordance with the emergency authorization.
6. The repairs removed sediment and repaired impacts to the roadway that resulted from the spring floods of 2006.

**2006-01180 GOFFSTOWN DEPARTMENT OF PUBLIC WORKS, TOWN OF
GOFFSTOWN**

Requested Action:

Emergency Authorization follow-up for after-the-fact approval to repair roadway side slopes adjacent to an existing stream culvert crossing and remove approximately 1,500 sq. ft. of sediment from the adjacent wetlands.

Conservation Commission/Staff Comments:

1. The Conservation Commission did not submit comments.
2. The New Hampshire Fish & Game Department did not submit comments.

CONFIRM EMERGENCY AUTHORIZATION:

Emergency Authorization follow-up for after-the-fact approval to repair roadway side slopes adjacent to an existing stream culvert crossing and remove approximately 1,500 sq. ft. of sediment from the adjacent wetlands.

With Conditions:

1. Any further alteration of areas on this property that are within the jurisdiction of the DES Wetlands Bureau will require a new application and further permitting by the Bureau.

With Findings:

1. This project is classified as a Minimum impact project per Rule Env-Wt 303.04(o) Projects deemed minimum impact by the department based on the degree of environmental impact.
2. The project was necessary to repair Addison Road, provide safe access and stabilize the banks and bed of the stream.
3. Emergency authorization for this work was issued by DES Wetlands Bureau Staff on May 19, 2006.
4. Review of the report submitted pursuant the emergency authorization indicates that work has been completed in accordance with the emergency authorization.
5. The repairs were needed due to damage from the floods of the spring of 2006.

**2006-01197 GOFFSTOWN PUBLIC WORKS, TOWN OF
GOFFSTOWN Hardy Brook**

Requested Action:

Emergency Authorization follow-up for after-the-fact approval to repair roadway side slopes adjacent to an existing stream and wetlands and repair the culvert headwalls and remove approximately 750 sq. ft. of sediment from the adjacent wetlands and stream.

Conservation Commission/Staff Comments:

1. The Conservation Commission did not submit comments.
2. The New Hampshire Fish & Game Department did not submit comments.

CONFIRM EMERGENCY AUTHORIZATION:

Emergency Authorization follow-up for after-the-fact approval to repair roadway side slopes adjacent to an existing stream and wetlands and repair the culvert headwalls and remove approximately 750 sq. ft. of sediment from the adjacent wetlands and stream.

With Conditions:

1. Any further alteration of areas on this property that are within the jurisdiction of the DES Wetlands Bureau will require a new application and further permitting by the Bureau.

With Findings:

1. This project is classified as a Minimum impact project per Rule Env-Wt 303.04(o) Projects deemed minimum impact by the department based on the degree of environmental impact.
2. The project was necessary to repair East Dunbarton Road, provide safe access and stabilize the banks of the stream and adjacent wetlands.
3. Emergency authorization for this work was issued by DES Wetlands Bureau Staff on May 19, 2006.
4. Review of the report submitted pursuant the emergency authorization indicates that work has been completed in accordance with the emergency authorization.
5. The repairs were needed due to damage from the floods of the spring of 2006.

2006-01864 GOFFSTOWN, PUBLIC WORKS TOWN OF
GOFFSTOWN Unnamed Stream

Requested Action:

After-the-fact follow-up for an emergency authorization issued to stabilize 135 sq. ft. (45 linear ft.) of intermittent stream bank and slope adjacent to the Goffstown Landfill. The emergency repairs were needed to prevent further collapse of a failed slope resulting from the spring flood events of 2006. The failed slope was cleared, reshaped, lined with a 60 mil HDPE linear material and gabion baskets.

Conservation Commission/Staff Comments:

1. The Conservation Commission did not submit comments.
2. The New Hampshire Fish & Game Department did not submit comments.

CONFIRM EMERGENCY AUTHORIZATION:

After-the-fact follow-up for an emergency authorization issued to stabilize 135 sq. ft. (45 linear ft.) of intermittent stream bank and slope adjacent to the Goffstown Landfill. The emergency repairs were needed to prevent further collapse of a failed slope resulting from the spring flood events of 2006. The failed slope was cleared, reshaped, lined with a 60 mil HDPE linear material and gabion baskets.

With Conditions:

1. All work shall be in accordance with plans by the Town of Goffstown, plan sheet 2 of 7, revision dated May 22, 2006, and plan sheet 7 of 7, dated November 11, 2005, as received by the Department on October 18, 2006.
2. Any further alteration of areas on this property that are within the jurisdiction of the DES Wetlands Bureau will require a new application and further permitting by the Bureau.

With Findings:

1. This project is classified as a minimum impact project per Rule Env-Wt 303.04(n) projects that alter the course of or disturb less than 50 linear feet, measured along the thread of the channel, of an intermittent nontidal stream or its banks provided construction is performed during periods of non-flow.
2. The project was necessary to stabilize the intermittent stream bank and failing landfill side slope in order to prevent further damage to the landfill and adjacent intermittent stream.
3. Emergency authorization for this work was issued by DES Wetlands Bureau Staff on July 27, 2006.
4. Review of the report submitted pursuant the emergency authorization indicates that work has been completed in accordance with the emergency authorization.
5. All work in the Wetlands Bureau's jurisdiction has been completed.

2006-02228 CARLSON, BARTON
MELVIN VILLAGE Lake Winnepesaukee

Requested Action:

Repair/replace existing 6 ft x 6 ft crib supported 8 ft x 22 ft permanent pier on 160 ft of frontage in Melvin Village on Lake Winnepesaukee.

APPROVE PERMIT:

Repair/replace existing 6 ft x 6 ft crib supported 8 ft x 22 ft permanent pier on 160 ft of frontage in Melvin Village on Lake Winnepesaukee.

With Conditions:

1. All work shall be in accordance with plans dated October 13, 2006 by Barton K. Carlson as received by the Department on October 17, 2006.
2. This permit shall not be effective until it has been recorded with the Registry of Deeds Office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to installation.
3. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, maintained during construction, and shall remain until the area is stabilized.
4. Work authorized shall be carried out such that discharges shall be avoided in spawning or nursery areas during spawning seasons, and impacts to such areas shall be avoided or minimized to the maximum extent practicable during all times of the year.
5. Work shall be carried out in a time and manner such that disturbance to migratory waterfowl, particularly loons', breeding and nesting areas shall be avoided.
6. Repair shall maintain existing size, location and configuration.
7. This permit does not allow for maintenance dredging.
8. This shall be the only structure on this water frontage and all portions of the dock shall be at least 20 ft from abutting property lines or the imaginary extension of those lines into the water.
9. This permit to replace or repair existing structures shall not preclude the Department of Environmental Services from taking any enforcement action or revocation action if the Department of Environmental Services later determines that these "existing structures" were not previously permitted or grandfathered.
10. Additional expedited minimum impact applications shall be accepted for the subject property for a period of 12 months only if the applicant demonstrates by plan that the additional project(s) are wholly unrelated or separate from the original application and when considered with the original application are not classified as minor or major.
11. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(v) maintenance, repair, and replacement in-kind of existing doking structures.
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01. 3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.

2006-02383 MANCHESTER DEPT OF HIGHWAYS, CITY OF
MANCHESTER Cohas Brook

Requested Action:

Fill approximately 400 sq. ft. of stream bed (Cohas Brook) to repair and stabilize and existing center pier of Cohas Brook Bridge located on Cohas Avenue in Manchester. Damage is a result of heavy rains and high stream flow that occurred in the spring of 2006. Work to include installation of temporary sandbag cofferdams and placement of Class B stone around the entire pier.

Conservation Commission/Staff Comments:

The Conservation Commission approved the project.

APPROVE PERMIT:

Fill approximately 250 sq. ft. of stream bed (Cohas Brook) to repair and stabilize an existing center pier of Cohas Brook Bridge located on Cohas Avenue in Manchester. Damage is a result of heavy rains and high stream flow that occurred in the spring of 2006. Work to include installation of temporary sandbag cofferdams, placement of Class A stone on the up stream and down stream ends of the pier, installation of high strength geotextile and gravel base along the sides of the pier and placement of granite curbing over the material on each side of the pier.

With Conditions:

1. All work shall be in accordance with plans by Hoyle, Tanner & Associates, Inc., revision dated September 22, 2006, as received by the Department on September 26, 2006 and narratives prepared by the City of Manchester, Department of Highways dated September 21 and 22, 2006 as received by the Department on September 25 and 26, 2006.
2. Appropriate turbidity controls shall be installed prior to construction, shall be maintained during construction such that no turbidity escapes the immediate dredge and fill area, and shall remain until suspended particles have settled and the water at the work site has returned to normal clarity.
3. Any future work on this property that is within the jurisdiction of the DES Wetlands Bureau as specified in RSA 482-A will require a new application and approval by the Bureau.
4. There shall be no excavation or operation of construction equipment in flowing water.
5. Cofferdams shall not be installed during periods of high flow, whether due to seasonal runoff or precipitation. Once a cofferdam is fully effective, confined work can proceed.
6. Prior to commencing work on a substructure located within surface waters, a cofferdam shall be constructed to isolate the substructure work area from the surface waters.
7. Temporary cofferdams shall be entirely removed immediately following construction.
8. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
9. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
10. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).
10. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid prior to entering the construction area.
11. Faulty equipment shall be repaired prior to entering jurisdictional areas.
12. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
13. All refueling of equipment shall occur outside of surface waters or wetlands during construction.

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(x), Maintenance, repair or replacement of a nondocking structure.
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01. 3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.
5. The repair is needed to protect the structural integrity of the existing bridge pier.
6. The proposed repair is not a substantial change from the existing bridge pier footprint.
7. The New Hampshire Fish & Game Department, Nongame and Endangered Wildlife Program is in agreement with the approved repair design.

Requested Action:

Retain 2,250 sq. ft. of jurisdictional impacts for the filling of an isolated man-made pond. Restoration/creation of wetland totaling 2,775 sq. ft. on the property is addressed under separate cover as DES Wetlands File# 2004-2472.

Inspection Date: 08/23/2006 by David A Price

APPROVE AFTER THE FACT:

Retain 2,250 sq. ft. of jurisdictional impacts for the filling of an isolated man-made pond. Restoration/creation of wetland totaling 2,775 sq. ft. on the property is addressed under separate cover as DES Wetlands File# 2004-2472.

With Conditions:

1. The work shall be in accordance with plans and all descriptive details by NH Soil Consultants, Inc. dated September 2006, as received by the Department on September 18, 2006.
2. Any further alteration of DES Wetlands Bureau jurisdictional areas on this property will require a new application and further permitting by the DES Wetlands Bureau.
3. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and shall remain until the area is stabilized.

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(f), alteration of less than 3,000 square feet of surface waters/wetlands.
2. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
3. Restoration/creation of wetland totaling 2,775 sq. ft. on this property is a condition of approval and is addressed under separate cover.
4. This proposal meets the criteria of Chapter Wt 300 for approvable minimum impact projects.
5. This impact was the result of a misinterpretation of the rules and the law contained in Env-Wt 100-800 and RSA 482-A.

FORESTRY NOTIFICATION

2006-02599 EVANS FAMILY LTD PARTNERSHIP
LONDONDERRY Unnamed Stream

COMPLETE NOTIFICATION:
Londonderry Tax Map 17, Lot# 45

2006-02602 WELLINGTON, RICHARD
LEE Unnamed Stream

COMPLETE NOTIFICATION:
Lee Tax Map 31, Lot# 3 & 4

2006-02608 UNH WOODLANDS
DURHAM Unnamed Stream

COMPLETE NOTIFICATION:

Durham Tax Map 14, Lot# UNH

**2006-02614 CALANDRELLI, MAFALDA
LEMPSTER Unnamed Stream**

COMPLETE NOTIFICATION:

Lempster Tax Map 4, Lot# 292

**2006-02642 SINZIBUKWUD INC
GRAFTON Unnamed Stream**

COMPLETE NOTIFICATION:

Grafton Tax Map 15, Lot# 53 & 53-1

**2006-02664 WHITE SYLVANIA TRUST, C/O EDWARD HARDING TRUST
SANDWICH Unnamed Stream**

COMPLETE NOTIFICATION:

Sandwich Tax Map R2, Lot# 20

**2006-02665 HODGSON, JOHN & ELIZABETH
DORCHESTER Unnamed Stream**

COMPLETE NOTIFICATION:

Dorchester Tax Map 7, Lot# 357

**2006-02667 YANKEE FOREST LLC, C/O WAGNER FOREST MGT
MILAN Unnamed Stream**

COMPLETE NOTIFICATION:

Milan Tax Map 42 Lot# 02 Parcel M

**2006-02668 FELLOWS, ROB
PETERBOROUGH Unnamed Stream**

COMPLETE NOTIFICATION:

Peterboro Tax Map R5, Lot# 16

**2006-02669 RICHER, DANIEL
FRANCESTOWN Unnamed Stream**

COMPLETE NOTIFICATION:

Francetown Tax Map 5, Lot# 3

EXPEDITED MINIMUM

**2006-01408 WOLFEBORO, TOWN OF
WOLFEBORO Unnamed Stream**

Requested Action:

Dredge and fill 280 square feet of intermittent stream to replace existing 30-foot culvert with a proposed 33-inch x 50 foot culvert to widen existing road.

APPROVE PERMIT:

Dredge and fill 280 square feet of intermittent stream to replace existing 30-foot culvert with a proposed 33-inch x 50 foot culvert to widen existing road.

With Conditions:

1. All work shall be in accordance with plans by North Country Soil Services dated September 19, 2006, as received by the Department on September 28, 2006.
2. Any future work on this property that is within the jurisdiction of the DES Wetlands Bureau as specified in RSA 482-A will require a new application and approval by the Bureau.
3. Work shall be done during periods of non-flow.
4. Appropriate siltation/erosion controls shall be in place prior to construction, shall be maintained during construction, and remain until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
5. Appropriate turbidity controls shall be installed prior to construction, shall be maintained during construction such that no turbidity escapes the immediate dredge area, and shall remain until suspended particles have settled and the water at the work site has returned to normal clarity.
6. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
7. Proper headwalls shall be constructed within seven days of culvert installation.
8. Culvert outlets shall be protected in accordance with the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).
9. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
10. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(n), projects that alter the course of or disturb less than 50 linear feet, measured along the thread of the channel, of an intermittent nontidal stream channel or its banks provided construction is performed during periods of non-flow.
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.

**2006-01669 YOUNG, WALTER & CAROL
HAVERHILL Unnamed Wetland**

Requested Action:

Dredge and fill 1,400 square feet of emergent wetlands to remove accumulated debris at inlet and replace 200 linear feet of an existing 24-inch CMP culvert with a 180 linear foot drainage swale, 48-inch x 20-foot culvert, and drain manhole.

APPROVE PERMIT:

Dredge and fill 1,400 square feet of emergent wetlands to remove accumulated debris at inlet and replace 200 linear feet of an existing 24-inch CMP culvert with approximately 200 linear feet of created stream channel, 48-inch x 20-foot culvert, and modified drain manhole.

With Conditions:

1. All work shall be in accordance with plans by Hayner/Swanson, Inc. dated May 12, 2006 and revised though October 06, 2006, as received by the Department on October 12, 2006.
2. Work shall be done during low flow conditions.
3. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
4. Work shall be conducted in a manner so as to minimize turbidity and sedimentation.
5. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
6. The drain manhole shall be filled with concrete grout fill in the area below the invert.
7. Culverts shall be properly rip rapped.
8. Proper headwalls shall be constructed within seven days of culvert installation.
9. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January, 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August, 1992).
10. Materials used to emulate a natural channel bottom must be rounded and smooth stones similar to the natural stream substrate and shall not include angular rip-rap or gravel.
11. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid.
12. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
13. All refueling of equipment shall occur outside of surface waters or wetlands during construction.
14. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
15. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
16. Only native plant species shall be planted.
17. Seed mix shall be a wetland seed mix appropriate to the area and shall be applied in accordance with manufacturers specifications.
18. Mulch shall be natural straw or equivalent.
19. The permittee shall attempt to control invasive, weedy species such as purple loosestrife (*Lythrum salicaria*) and common reed (*Phragmites australis*) by measures agreed upon by the DES Wetlands Bureau if the species is found in the stream creation areas during construction and during the early stages of vegetative establishment.
20. The wetland creation area shall have at least 75% successful establishment of wetlands vegetation after two (2) growing seasons, or shall be replanted and re-established until a functional wetland is replicated in a manner satisfactory to the DES Wetlands Bureau.
21. Stream creation shall be properly constructed, landscaped, monitored and remedial actions taken that may be necessary to create a healthy riverine system. Remedial measures may include replanting, relocating plantings, removal of invasive species, changing stream sinuosity, changing the slope of the stream, and changing the hydrologic regime.
22. The permittee shall designate a qualified professional who will be responsible for monitoring and ensuring that the creation area is constructed in accordance with the creation plan. Monitoring shall be accomplished in a timely fashion and remedial measures taken if necessary. The DES Wetlands Bureau shall be notified in writing of the designated professional prior to the start of work and if there is a change of status during the project.
23. The permittee or a designee shall conduct a follow-up inspection after the first growing season, to review the success of the

creation area and schedule remedial actions if necessary. A report outlining these follow-up measures and a schedule for completing the remedial work shall be submitted by December 1 of that year. Similar inspections, reports and remedial actions shall be undertaken in at least the second year following the completion of the creation site.

24. A post-construction report documenting the status of the restored jurisdictional area, including photographs shall be submitted to the Wetlands DES within 60 days of the completion of construction.

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(f), alteration of less than 3,000 square feet of wetlands.
2. Property owners, Walter and Carol Young, have granted a drainage easement on their property for the runoff from the pipe that outlets south of Forest Street.
3. The stormwater upgrades east of the proposed impact area will not impact jurisdictional areas. The applicant has indicated flow is stormwater runoff only.
4. The applicant has agreed to a created stream channel to replace the 200 linear feet of the 24-inch CMP culvert.
5. This permit is contingent on concrete grout fill in the area of the drain manhole below the invert to allow for wildlife passage.
6. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01. 7. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
8. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.

2006-02056 CERSOSIMO INDUSTRIES INC
FRANCESTOWN Unnamed Wetland

Requested Action:

Dredge 2,172 square feet of palustrine forested wetlands to construct an approximately 9,000 square foot fire pond and associated spillway and dry hydrant for a 5-lot residential subdivision on an approximately 37 acre parcel with approximately 19 acres of "green space".

Conservation Commission/Staff Comments:

The Conservation Commission signed the application but did not submit comments.

APPROVE PERMIT:

Dredge 2,172 square feet of palustrine forested wetlands to construct an approximately 9,000 square foot fire pond and associated spillway and dry hydrant for a 5-lot residential subdivision on an approximately 37 acre parcel with approximately 19 acres of "green space".

With Conditions:

1. All work shall be in accordance with plans by RCS Designs dated July 15, 2006 as received by the DES Wetlands Bureau on August 15, 2006 and plans by SVE Associates dated July 17, 2006 and September 5, 2006, as received on September 18, 2006.
2. This permit is contingent on approval by the DES Subsurface Systems Bureau.
3. This permit shall not be effective until it has been recorded with the Hillsborough County Registry of Deeds by the Permittee and a copy of the registered permit has been received by the DES Wetlands Bureau.
4. The deed which accompanies the sales transaction of each lot in this subdivision shall contain condition #5 of this approval.
5. There shall be no further alteration of wetlands for lot development, driveways, culverts, or for septic setback.
6. All work shall be done during low flow.
7. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
8. Dredged material shall be dewatered in sedimentation basins located outside of the jurisdiction of the DES Wetlands Bureau. The dewatering area shall be lined with siltation and erosion controls to prevent runoff from entering jurisdictional areas.
9. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.

10. The contractor responsible for completion of the work shall utilize techniques described in the DES Best Management Practices for Urban Stormwater Runoff Manual (January 1996) and the Stormwater Management and Erosion and Sediment Control Handbook for Urban and Developing Areas in New Hampshire (August 1992).
11. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain until the area is stabilized.
12. Silt fence(s) must be removed once the area is stabilized.
13. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
14. Construction equipment shall be inspected daily for leaking fuel, oil, and hydraulic fluid prior to entering or working near surface waters or wetlands.
15. Faulty equipment shall be repaired prior to entering or working near jurisdictional areas.
16. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
17. All refueling of equipment shall occur outside of surface waters or wetlands during construction.
18. Additional expedited minimum impact applications shall be accepted for the subject property for a period of 12 months only if the applicant demonstrates by plan that the additional project(s) are wholly unrelated or separate from the original application and when considered with the original application are not classified as minor or major.

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(f), projects involving alteration of less than 3,000 square feet in swamps or wet meadows that are not in prime wetlands or do not meet the requirements of Env-Wt 303.02(k), provided that no previous department permit has placed restrictions on the property of the applicant.
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01. The impacts are necessary for the construction of a fire pond for a 5-lot residential subdivision.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the DES Wetlands Bureau's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.
5. An access road from 2nd New Hampshire Turnpike is being constructed for access to the dry hydrant.
6. This permit is contingent on approval by the DES Subsurface Systems Bureau.
7. The Conservation Commission signed the application but did not submit comments.

2006-02171 SCHUSSEL, GEORGE
MEREDITH Lake Winnepesaukee

Requested Action:

Replace an existing 128 ft retaining wall with 128 ft dry stone wall on property having 1,977 feet of frontage in Advent Cove, on Lake Winnepesaukee, Meredith.

Conservation Commission/Staff Comments:

Con Com signed Exp Application

APPROVE PERMIT:

Replace an existing 128 ft retaining wall with 128 ft dry stone wall on property having 1,977 feet of frontage in Advent Cove, on Lake Winnepesaukee, Meredith.

With Conditions:

1. All work shall be in accordance with site plans by as received by the Department on August 24, 2006.
2. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
3. Repair shall maintain existing size, location and configuration.

4. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
5. Work shall be done during drawdown.
6. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This project is classified as a minimum impact project per Rule Env-Wt 303.04(v), repair of existing structures with no change in size, location or configuration.

**2006-02197 NH DEPT OF TRANSPORTATION
BEDFORD Unnamed Wetland**

Requested Action:

Dredge and fill approximately 516 sq. ft. (132 sq. ft. of permanent impact and 384 sq. ft. temporary impact) of wetlands for the installation of approximately 4,692 linear ft. of sewer line for a proposed workout club & wellness center.

Conservation Commission/Staff Comments:

The Bedford Conservation Commission approved the proposed project.

APPROVE PERMIT:

Dredge and fill approximately 516 sq. ft. (132 sq. ft. of permanent impact and 384 sq. ft. temporary impact) of wetlands for the installation of approximately 4,692 linear ft. of sewer line for a proposed workout club & wellness center.

With Conditions:

1. All work shall be in accordance with plans and narratives by TFMoran Inc., plan sheet 16 of 29 revision dated July 13, 2006 as received by the Department on August 25 2006, plan sheets 3 and 4 of 29, revision dated July 25, 2006, plan sheets 26, 27, 28 and 29 of 29 revision dated September 26, 2006 as received by the Department on October 23, 2006.
2. The temporary wetlands impact area shall be regraded to original contours following completion of work and re-planted with a native wetland seed mix. The temporary impact restoration shall be supervised by a certified wetland scientist.
3. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and shall remain until the area is stabilized. Silt fencing must be removed once the area is stabilized.
4. This permit is contingent on approval by the DES Site Specific Program.
5. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
6. Within three days of final grading in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
7. Where construction activities have been temporarily suspended within the growing season, all exposed soil areas shall be stabilized within 14 days by seeding and mulching.
8. Where construction activities have been temporarily suspended outside the growing season, all exposed areas shall be stabilized within 14 days by mulching and tack. Slopes steeper than 3:1 shall be stabilized by matting and pinning.

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(f), alteration of less than 3,000 sq. ft. of wetlands.
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01. 3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.
5. The applicant provided documentation from the NH Department of Transportation ("DOT") approving the proposed work within the DOT right-of-way.

2006-02259 FRANCETOWN, TOWN OF
FRANCETOWN Unnamed Wetland

Requested Action:

Dredge and fill approximately 60 sq. ft. of perennial stream bed and bank and wetlands to install a 36 in. x 30 ft. overflow culvert adjacent to an existing 36 in. x 30 ft. stream culvert. Work includes installation of the proposed culvert, new culvert headwalls and re-construction of the outlet plunge pool area.

Conservation Commission/Staff Comments:

1. The Conservation Commission submitted comments requesting DES issue the permit due to flood concerns.
2. The New Hampshire Fish & Game Department did not submit comments.

APPROVE PERMIT:

Dredge and fill approximately 60 sq. ft. of perennial stream bed and bank and wetlands to install a 36 in. x 30 ft. overflow culvert adjacent to an existing 36 in. x 30 ft. stream culvert. Work includes installation of the proposed culvert, new culvert headwalls and re-construction of the outlet plunge pool area.

With Conditions:

1. All work shall be in accordance with plans by the Town of Francetown, Dept. of Public Works, Road Surface and Headwall cross section plan received by the department on September 6, 2006, and plans dated October 18, 2006 as received by the Department on October 20, 2006.
2. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
3. Appropriate turbidity controls shall be installed prior to construction, shall be maintained during construction such that no turbidity escapes the immediate dredge area, and shall remain until suspended particles have settled and the water at the work site has returned to normal clarity.
4. Work shall be done during low flow conditions.
5. All in-stream work shall be conducted in a manner that minimizes the duration of construction in the watercourse. In-stream work shall not exceed five consecutive days in total unless specifically authorized in writing by the Wetlands Bureau.
6. There shall be no excavation or operation of construction equipment in flowing water.
7. Prior to commencing work on a substructure located within surface waters, a cofferdam shall be constructed to isolate the substructure work area from the surface waters.
8. Temporary cofferdams shall be entirely removed immediately following construction.
9. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
10. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
11. Proper headwalls shall be constructed within seven days of culvert installation.
12. Any further alteration of areas on this property that are within the jurisdiction of the DES Wetlands Bureau will require a new application and further permitting by the Bureau.
13. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid. Faulty equipment shall be repaired immediately.
14. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
15. All refueling of equipment shall occur outside of surface waters or wetlands during construction.

With Findings:

1. This project is classified as a minimum impact project per Rule Env-Wt 303.04(o) Projects deemed minimum impact by the department based on the degree of environmental impact.
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01.
3. The current culvert will not be impacted by the proposed overflow culvert.

4. The existing culvert outlet is approximately 2 feet higher than the natural stream bed.
5. The proposed slope impact for the culvert installation currently consists of roadway side slope and culvert headwall material.
6. The Conservation Commission submitted comments requesting DES issue the permit due to flood concerns.
7. The New Hampshire Fish & Game Department did not submit comments.

2006-02397 ATKINS, BRANDT
SOMERSWORTH Unnamed Pond

Requested Action:

Impact 650 sq. ft. of wetlands to construct a weir at outlet of existing man-made detention pond to improve drainage control from the pond into the adjacent wetlands.

APPROVE PERMIT:

Impact 650 sq. ft. of wetlands to construct a weir at outlet of existing man-made detention pond to improve drainage control from the pond into the adjacent wetlands.

With Conditions:

1. All work shall be in accordance with plans by Tritech Engineering Inc. dated 8/17/2006, as received by the Department on 9/19/2006.
2. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
3. There shall be no further alteration of wetlands for lot development, driveways, culverts, or for septic setback.
4. Orange construction fencing shall be placed at the limits of construction to prevent accidental encroachment on wetlands.
5. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
6. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.
7. Work shall be done during low flow.

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(f), projects involving alteration of less than 3,000 sq. ft. of swamps or wet meadows.
2. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01.
3. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
4. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.
5. Maintenance dredging of the man-made detention pond does not require a permit pursuant to RSA 482-A:3 IV, (b).

2006-02402 SCARBOROUGH, JAMES & SUSAN
WOLFEBORO Lake Winnepesaukee

Requested Action:

Repair an existing 21 ft by 5 ft 10 in permanent dock supported by a 12 ft by 5 ft crib, attached to an existing 34 ft wharf supported by a 7 ft by 33 ft crib on Lake Winnepesaukee, Wolfeboro.

Conservation Commission/Staff Comments:

Con Com signed Exp Application

APPROVE PERMIT:

Repair an existing 21 ft by 5 ft 10 in permanent dock supported by a 12 ft by 5 ft crib, attached to an existing 34 ft wharf supported by a 7 ft by 33 ft crib on Lake Winnepesaukee, Wolfeboro.

With Conditions:

1. All work shall be in accordance with plans by Folsom Design Group dated August 25, 2006, as received by the Department on September 20, 2006.
2. This permit shall not be effective until it has been recorded with the Registry of Deeds Office by the Permittee. A copy of the registered permit shall be submitted to the DES Wetlands Bureau prior to construction.
3. This permit to replace or repair existing structures shall not preclude the Department of Environmental Services from taking any enforcement action or revocation action if the Department of Environmental Services later determines that these "existing structures" were not previously permitted or grandfathered.
4. Repair shall maintain existing size, location and configuration.
5. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, maintained during construction, and shall remain until the area is stabilized.
6. Work authorized shall be carried out such that discharges in spawning or nursery areas during spawning seasons shall be avoided, and impacts to such areas shall be avoided or minimized to the maximum extent practicable during all times of the year.
7. Work shall be carried out in a time and manner such that disturbance to migratory waterfowl breeding areas and spawning areas shall be avoided.
8. Additional expedited minimum impact applications shall be accepted for the subject property for a period of 12 months only if the applicant demonstrates by plan that the additional project(s) are wholly unrelated or separate from the original application and when considered with the original application are not classified as minor or major.
9. Dredged material shall be placed outside of the jurisdiction of the DES Wetlands Bureau.
10. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This project is classified as a minimum impact project per Rule Env-Wt 303.04(v), repair of existing structures with no change in size, location or configuration.

**2006-02405 MORSE, ROBERT & SUSAN
SANBORNVILLE Lovell Lake**

Requested Action:

Repair and replace in-kind an existing 60 ft of retaining wall on 100 ft of frontage on Lovell Lake, Sanbornville.

Conservation Commission/Staff Comments:

Con Com signed Exp Application

APPROVE PERMIT:

Repair and replace in-kind an existing 60 ft of retaining wall on 100 ft of frontage on Lovell Lake, Sanbornville.

With Conditions:

1. All work shall be in accordance with plans by Relf Fogg, as received by the Department on September 20, 2006.
2. This permit shall not preclude the Department of Environmental Services (DES) from taking any enforcement action or revocation action if the DES later determines that these "existing structures" were not previously permitted or grandfathered.
3. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and remain in place until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
4. Work shall be done during drawdown.
5. Area shall be regraded to original contours following completion of work.
6. Repair shall maintain existing size, location and configuration.
7. Retaining wall shall be constructed landward of the shoreline defined by the elevation of normal high water so as not to create land in public water.

8. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This project is classified as a minimum impact project per Rule Env-Wt 303.04(v), repair of existing structures with no change in size, location or configuration.

2006-02411 POTTER, ALLAN
MIDDLETON Sunrise Lake

Requested Action:

Construct a 540 sqft perched beach with less than 10 cubic yards of sand and 3 ft access stairs on Sunrise Lake, Middleton.

Conservation Commission/Staff Comments:

Con Com signed Exp Application

NH NHI and NH Fish and Game will not be submitting comments

APPROVE PERMIT:

Construct a 540 sqft perched beach with less than 10 cubic yards of sand and 3 ft access stairs on Sunrise Lake, Middleton.

With Conditions:

1. All work shall be in accordance with plans by Randy Orvis dated September 5, 2006, as received by the Department on September 21, 2006.
2. Dredged or excavated material shall be placed outside of the DES Wetlands Bureau jurisdiction.
3. Stone placed along the beach front for the purpose of retaining sand shall be placed above and/or landward of those rocks currently located along the normal high water line (Elevation 92.5). Those rocks existing at the normal high water line shall remain otherwise undisturbed such that the natural shoreline remains identifiable.
4. The steps installed for access to the water shall be located completely landward of the normal high water line.
5. No more than 10 cu. yds. of sand may be used and all sand shall be located above the normal high water line.
6. This permit shall be used only once, and does not allow for annual beach replenishment.
7. The permittee shall provide appropriate diversion of surface water runoff to prevent erosion of beach area.
8. Revegetation of trees, shrubs and ground covers representing the density and species diversity of the existing stand of vegetation removed for this project shall begin at a distance no greater than 5 feet landward from the beach area.
9. Appropriate siltation/erosion/turbidity controls shall be in place prior to construction, shall be maintained during construction, and shall remain until the area is stabilized.
10. All activity shall be in accordance with the Comprehensive Shoreland Protection Act, RSA 483-B (see attached fact sheet).

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(d), construction of a beach.
2. NH NHI and NH Fish and Game will not be submitting comments.

2006-02468 MOUNTAIN LAKES DISTRICT
HAVERHILL Mountain Lake North

Requested Action:

Dredge and fill 150 square feet of Lower Mountain Lake for existing dam repairs, including slip-lining existing 24-inch CMP with an 18-inch HDPE culvert and replacing the existing 24-inch shear gate. Temporarily impact 1,750 square feet for work space.

APPROVE PERMIT:

Dredge and fill 150 square feet of Lower Mountain Lake for existing dam repairs, including slip-lining existing 24-inch CMP with

an 18-inch HDPE culvert and replacing the existing 24-inch shear gate. Temporarily impact 1,750 square feet for work space.

With Conditions:

1. All work shall be in accordance with plans by Dubois and King, Inc. dated August 22, 2006, as received by the Department on September 18, 2006.
2. This permit is contingent on approval by the DES Dam Safety Program.
3. This permit is contingent on review and written approval, by the DES Wetlands Bureau, of the final sheet pile cofferdam design, final sheet pile retaining wall design, and the final means and methods for abandoning the existing water main in-place.
4. The proposed drawdown shall be completed before November 17, 2006.
5. No in-stream work shall occur after November 17, 2006 unless a waiver of this condition is issued by the DES Wetlands Bureau in consultation with the NH Department of Fish and Game.
6. Appropriate siltation/erosion controls shall be in place prior to construction, shall be maintained during construction, and remain until the area is stabilized. Silt fence(s) must be removed once the area is stabilized.
7. Appropriate turbidity controls shall be installed prior to construction, shall be maintained during construction such that no turbidity escapes the immediate work area, and shall remain until suspended particles have settled and the water at the work site has returned to normal clarity.
8. Work shall be conducted in a manner so as to minimize turbidity and sedimentation.
9. There shall be no excavation or operation of construction equipment in flowing water.
10. Prior to commencing work on a substructure located within surface waters, a cofferdam shall be constructed to isolate the substructure work area from the surface waters.
11. Dewatering of work areas or of dredge materials, if required, shall be conducted in a manner so as to prevent turbidity.
12. Discharge from dewatering of work areas shall be to sediment basins that are: a) located in uplands; b) lined with hay bales or other acceptable sediment trapping liners; c) set back as far as possible from wetlands and surface waters, in all cases with a minimum of 20 feet of undisturbed vegetated buffer.
13. Work within the stream, inclusive of work associated with installation of a cofferdam, shall be done during periods of low flow. High flows can be caused by seasonal runoff or precipitation; the permittee shall monitor local forecasts to review weather conditions.
14. No work within the confined area shall proceed until the cofferdam is fully effective, and water flow is controlled.
15. Temporary cofferdams shall be entirely removed immediately following construction.
16. Construction equipment shall be inspected daily for leaking fuel, oil and hydraulic fluid prior to entering surface waters or wetlands. Faulty equipment shall be repaired prior to entering jurisdictional areas.
17. The contractor shall have appropriate oil spill kits on site and readily accessible at all times during construction and each operator shall be trained in its use.
18. All refueling of equipment shall occur outside of surface waters or wetlands during construction.
19. Within three days of final grading or temporary suspension of work in an area that is in or adjacent to wetlands or surface waters, all exposed soil areas shall be stabilized by seeding and mulching during the growing season, or if not within the growing season, by mulching with tack or netting and pinning on slopes steeper than 3:1.

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(x), maintenance, repair, or replacement of a dam.
2. The DES Dam Safety Program issued a letter of deficiency regarding proposed repairs.
3. The NH Fish and Game Department agreed to the proposed drawdown and construction schedule.
4. This permit is contingent on the completion of in-stream work and the proposed drawdown by November 17, 2006.
5. The need for the proposed impacts has been demonstrated by the applicant per Env-Wt 302.01. 6. The applicant has provided evidence which demonstrates that this proposal is the alternative with the least adverse impact to areas and environments under the department's jurisdiction per Env-Wt 302.03.
7. The applicant has demonstrated by plan and example that each factor listed in Env-Wt 302.04(b) Requirements for Application Evaluation, has been considered in the design of the project.

TRAILS NOTIFICATION

2006-02606 BROOKS, JON
NEW BOSTON Unnamed Stream

COMPLETE NOTIFICATION:
New Boston Tax Map 4, Lot# 69

2006-02616 RABTOY, AGNES
UNITY Unnamed Stream

COMPLETE NOTIFICATION:
Unity Tax Map/Lot# 11 / 732 & 16 / 513 & 825

2006-02643 GOLF MANAGEMENT CO
EPPING Unnamed Stream

COMPLETE NOTIFICATION:
Epping Tax Map 30, Lot# 30

2006-02688 DRED, SANDY YOUNG
PITTSBURG Unnamed Stream

COMPLETE NOTIFICATION:
Pittsburg Tax MAp 1, Lot# 26

LAKES-SEASONAL DOCK NOTIF

2006-02671 FOGEL, JEFF
NEWBURY Sunapee Lake

COMPLETE NOTIFICATION:
Newbury NH Tax Map# 19 Lot# 430 Block# 569 Sunapee Lake

2006-02686 LONG, RUTH
MOULTONBOROUGH Winnepesaukee Lake

COMPLETE NOTIFICATION:
Moultonborough NH Tax Map# 219 Lot# 002 Lake
Winnepesaukee

ROADWAY MAINTENANCE NOTIF

**2006-02663 NH DEPT OF TRANSPORTATION
SANDWICH Unnamed Stream**

**2006-02666 HANCOCK, TOWN OF
HANCOCK Unnamed Stream**

PERMIT BY NOTIFICATION

**2006-01703 HANOVER, JACK
GILFORD Lake Winnepesaukee**

Requested Action:
Straighten out and repair/replace existing breakwater.

PBN DISQUALIFIED:
Straighten out and repair/replace existing breakwater.

With Findings:
1. Modification to a breakwater is considered a major project as per rule 303.02(d) therefore this PBN has been disqualified from the process.

Requested Action:
Repair/Replace existing breakwater "in-kind".

PBN IS COMPLETE:
Repair/Replace existing breakwater "in-kind".

With Findings:
1. This project is classified as a minimum impact project per Rule Env-Wt 303.04(v), repair of existing structures with no change in size, location or configuration.

**2006-02440 GARBARINO, DAVID
WOLFEBORO Lake Winnepesaukee**

Requested Action:
Repair existing crib supported dock.

PBN IS COMPLETE:
Repair existing crib supported dock.

With Findings:

1. This project is classified as a minimum impact project per Rule Env-Wt 303.04(v), repair of existing structures with no change in size, location or configuration.

2006-02517 JUVONEN, WILLIAM & KAREN
WOLFEBORO Lake Winnepesaukee

Requested Action:
repair/replace existing crib supported docking facility.

PBN IS COMPLETE:
repair/replace existing crib supported docking facility.

With Findings:

1. This project is classified as a minimum impact project per Rule Env-Wt 303.04(v), repair of existing structures with no change in size, location or configuration.

2006-02620 OSRAM SYLVANIA INC.
EXETER Unnamed Wetland

Requested Action:
Dredge 480 square feet of an existing drainage swale for continued usefulness.

Conservation Commission/Staff Comments:
The Exeter Conservation Commission signed the PBN.

PBN IS COMPLETE:
Dredge 480 square feet of an existing drainage swale for continued usefulness.

With Findings:

1. This is a minimum impact project per Administrative Rule Env-Wt 303.04(k) Maintenance dredging, when necessary to provide continued usefulness of nontidal drainage ditches, man-made ponds, and spillways.

2006-02657 BELMONT, JUDSON & JANICE
MEREDITH Lake Winnisquam

Requested Action:
Repair/replace existing perched beach.

PBN IS COMPLETE:
Repair/replace existing perched beach.

With Findings:

1. This project is classified as a minimum impact project per Rule Env-Wt 303.04(v), repair of existing structures with no change in size, location or configuration.

2006-02659 BAGGE, HAROLD & PAULA
WOLFEBORO Lake Winnepesaukee

Requested Action:

Repair/Replace existing permanent docking facility, stabilize the bank, and reinstall dock access stairs "in-kind".

PBN IS COMPLETE:

Repair/Replace existing permanent docking facility, stabilize the bank, and reinstall dock access stairs "in-kind".

With Findings:

1. This project is classified as a minimum impact project per Rule Env-Wt 303.04(v), repair of existing structures with no change in size, location or configuration.

2006-02673 TOURTELOTTE, JOHN & JANE O'TOOLE
ALTON Lake Winnepesaukee

Requested Action:

Repair replace shoreline structures in kind.

PBN IS COMPLETE:

Repair replace shoreline structures in kind.

With Findings:

1. This project is classified as a minimum impact project per Rule Env-Wt 303.04(v), repair of existing structures with no change in size, location or configuration.